

View Online at <https://aerobasegroup.com/nsn/3120-01-363-1796>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Bore Diameter:

Between 0.7495 inches and 0.7500 inches

Outer Member Outside Diameter:

Between 1.7400 inches and 1.7850 inches

Bore Center To Shank End Distance:

Between 2.8650 inches and 2.8850 inches

Outer Member Width:

Between 0.8740 inches and 0.8760 inches

Inner Member Width:

Between 0.6350 inches and 0.6450 inches

Shank End To Shoulder Length:

Between 1.7200 inches and 1.8100 inches

Shank Thread Length:

Between 1.7200 inches and 1.8100 inches

Static Radial Load Rating:

30000 pounds

Thread Diameter:

0.750 inches

Thready Qty Per Inch (tpi):

16

Material:

Steel comp 630

Material Specification:

Ams 5643 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type i, class 2 federal specification single treatment response

Style Designator:

Shouldered flange type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0