

View Online at <https://aerobasegroup.com/nsn/3120-01-368-6150>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Overall Length:

2.7000 inches

Bore Diameter:

Between 0.4370 inches and 0.4375 inches

Outer Member Outside Diameter:

Between 1.1400 inches and 1.1600 inches

Bore Center To Shank End Distance:

Between 2.1150 inches and 2.1350 inches

Outer Member Width:

Between 0.4470 inches and 0.4570 inches

Inner Member Width:

Between 0.5600 inches and 0.5620 inches

Shank Thread Length:

Between 1.2500 inches and 1.3120 inches

Thread Diameter:

0.4375 inches

Thready Qty Per Inch (tpi):

14

Hardness Rating:

55.0 rockwell c inner member and 62.0 rockwell c inner member 28.0 rockwell c race insert and 37.0 rockwell c race insert 39.0 rockwell c rod end body and 42.0 rockwell c rod end body

Material:

Steel comp 440c inner member steel comp 630 race insert plastic polytetrafluoroethylene race liner steel comp e4340 rod end body

Surface Treatment:

Cadmium rod end body and chromate rod end body

Style Designator:

Ball type

Thread Series Designator:

Unj

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0