

View Online at <https://aerobasegroup.com/nsn/3120-01-383-7395>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Style:

Externally threaded

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

End Application:

Pacer dawn

Outer Member Outside Diameter:

Between 0.8170 inches and 0.8370 inches

Bore Center To Shank End Distance:

Between 1.4330 inches and 1.4530 inches

Outer Member Width:

Between 0.2550 inches and 0.2650 inches

Inner Member Width:

Between 0.3410 inches and 0.3430 inches

Shank Thread Length:

Between 0.7440 inches and 0.8060 inches

Thread Diameter:

Between 0.7440 inches and 0.8060 inches

Thready Qty Per Inch (tpi):

28

Keyway Dimension:

0.2020 inches internal keyway depth and 0.2070 inches internal keyway depth

Special Features:

Bearing is self-aligning and selflubricating

Material:

Steel comp 4340

Material Specification:

Mil-s-5000 military specification single material response

Style Designator:

Shouldered ball type

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0

Mil-std (military Standard):

Mil-s-5000 spec.