

View Online at <https://aerobasegroup.com/nsn/3120-01-383-7395>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Style:**

Externally threaded

**Bore Diameter:**

Between 0.2495 inches and 0.2500 inches

**End Application:**

Pacer dawn

**Outer Member Outside Diameter:**

Between 0.8170 inches and 0.8370 inches

**Bore Center To Shank End Distance:**

Between 1.4330 inches and 1.4530 inches

**Outer Member Width:**

Between 0.2550 inches and 0.2650 inches

**Inner Member Width:**

Between 0.3410 inches and 0.3430 inches

**Shank Thread Length:**

Between 0.7440 inches and 0.8060 inches

**Thread Diameter:**

Between 0.7440 inches and 0.8060 inches

**Thready Qty Per Inch (tpi):**

28

**Keyway Dimension:**

0.2020 inches internal keyway depth and 0.2070 inches internal keyway depth

**Special Features:**

Bearing is self-aligning and selflubricating

**Material:**

Steel comp 4340

**Material Specification:**

Mil-s-5000 military specification single material response

**Style Designator:**

Shouldered ball type

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0

**Mil-std (military Standard):**

Mil-s-5000 spec.