## NSN 3120-01-389-9148

Rod End Plain Bearing - Page 1 of 2



**Thread Class:** 3a **Thread Direction: Right-hand** Shank Style: Externally threaded **Overall Length:** 2.4380 inches **Bore Diameter:** Between 0.2495 inches and 0.2500 inches **Outer Member Outside Diameter:** Between 0.9900 inches and 1.0100 inches **Bore Center To Shank End Distance:** Between 1.9390 inches and 2.0320 inches **Outer Member Width:** Between 0.2600 inches and 0.2720 inches **Inner Member Width:** Between 0.5880 inches and 0.5930 inches Shank Thread Length: Between 1.2190 inches and 1.3120 inches **Static Radial Load Rating:** 2270 pounds **Thread Diameter:** 0.3750 inches Thready Qty Per Inch (tpi): 24 **Lubrication Feature:** Self-lubricating liner race liner **Special Features:** Straight knurl over threads Material: Steel comp 630 race insert Surface Treatment: Passivate inner member Style Designator: Ball type **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure:

---



## NSN 3120-01-389-9148

Rod End Plain Bearing - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A045a0

