## NSN 3120-01-464-4212

Sleeve Bushing - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/3120-01-464-42    |
|----------------------------------------------------------------|
| Overall Length:                                                |
| Between 0.7450 inches and 0.7550 inches                        |
| Body Outside Diameter:                                         |
| Between 0.4381 inches and 0.4386 inches                        |
| Body Inside Diameter:                                          |
| Between 0.3125 inches and 0.3140 inches                        |
| Flange Outside Diameter:                                       |
| Between 0.5520 inches and 0.5720 inches                        |
| Flange Width:                                                  |
| Between 0.0570 inches and 0.0620 inches                        |
| Corner Shape:                                                  |
| Square all corners                                             |
| Product Name:                                                  |
| Bushing-flanged, press fit steel, bronze, and copper           |
| Material:                                                      |
| Steel comp 4130                                                |
| Material Specification:                                        |
| Mil-s-6758 military specification all material responses       |
| Surface Treatment:                                             |
| Cadmium                                                        |
| Surface Treatment Specification:                               |
| Qq-p-416, ty2cl2 federal specification all treatment responses |
| Style Designator:                                              |
| 22c solid, external flange one end                             |
| Shelf Life:                                                    |
| N/a                                                            |
| Unit Of Measure:                                               |
|                                                                |
| Demilitarization:                                              |
| No                                                             |
| Fiig:                                                          |
| A045a0                                                         |

Mil-std (military Standard):

Mil-s-6758 spec.