

View Online at <https://aerobasegroup.com/nsn/3120-01-466-0316>

Hole Diameter:

0.1935 inches first

Overall Length:

5.5000 inches

Body Outside Diameter:

Between 0.9984 inches and 0.9989 inches

Body Inside Diameter:

0.7350 inches

End Application:

Nha I5845501-101 hydraulic equipment installation-main landing gear, deck, station; t.O. 1b-1b-4-32, fig 19, index 261/2

Corner Shape:

Square inside left corner

Surface Finish:

8.0 microinches outside diameter surface of body

Antirotation/lubrication Type And Quantity:

2 hole

Special Features:

Suggested name pin-wheel axle beam ramp, mlg belved lockdown extensions either end 0.50 inches wide x 0.50 inches long x 0.130 inches thick with hole of ctmj

Material:

Steel

Surface Treatment:

Nickel and chromate

Surface Treatment Specification:

Mil-c-26074, cl1 military specification 1st treatment response and qq-c-320, cl2 military specification 2nd treatment response

Style Designator:

17c solid, plain, no outside flanges

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A045a0

Mil-std (military Standard):

Mil-c-26074 spec.