

View Online at <https://aerobasegroup.com/nsn/3120-01-466-0316>

**Hole Diameter:**

0.1935 inches first

**Overall Length:**

5.5000 inches

**Body Outside Diameter:**

Between 0.9984 inches and 0.9989 inches

**Body Inside Diameter:**

0.7350 inches

**End Application:**

Nha I5845501-101 hydraulic equipment installation-main landing gear, deck, station; t.O. 1b-1b-4-32, fig 19, index 261/2

**Corner Shape:**

Square inside left corner

**Surface Finish:**

8.0 microinches outside diameter surface of body

**Antirotation/lubrication Type And Quantity:**

2 hole

**Special Features:**

Suggested name pin-wheel axle beam ramp, mlg belved lockdown extensions either end 0.50 inches wide x 0.50 inches long x 0.130 inches thick with hole of ctmj

**Material:**

Steel

**Surface Treatment:**

Nickel and chromate

**Surface Treatment Specification:**

Mil-c-26074, cl1 military specification 1st treatment response and qq-c-320, cl2 military specification 2nd treatment response

**Style Designator:**

17c solid, plain, no outside flanges

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A045a0

**Mil-std (military Standard):**

Mil-c-26074 spec.