

View Online at <https://aerobasegroup.com/nsn/3120-01-478-9414>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Style:

Internally threaded w/hexagon end and inspection hole

Overall Length:

Between 1.6670 inches and 1.7070 inches

Bore Diameter:

Between 0.2495 inches and 0.2515 inches

Outer Member Outside Diameter:

Between 0.7400 inches and 0.7600 inches

Bore Center To Shank End Distance:

Between 1.3020 inches and 1.3220 inches

Outer Member Width:

Between 0.2760 inches and 0.2860 inches

Inner Member Width:

Between 0.3700 inches and 0.3750 inches

Shank Thread Length:

0.7500 inches

Inspection Hole Center To End Distance:

Between 0.3070 inches and 0.3170 inches

Shank Width Across Wrench Flats:

Between 0.3650 inches and 0.3850 inches

Static Radial Load Rating:

1550 pounds

Thread Diameter:

Between 0.2472 inches and 0.2500 inches

Thready Qty Per Inch (tpi):

3

Lubrication Feature:

Self-lubricating liner race liner

Material:

Steel rod end body

Style Designator:

Ball type

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A045a0