

View Online at <https://aerobasegroup.com/nsn/3120-01-483-2240>

**Thread Class:**

3b

**Shank Diameter:**

Between 0.6220 inches and 0.6280 inches

**Shank Style:**

Internally threaded w/inspection hole

**Overall Length:**

Between 1.7080 inches and 1.7280 inches

**End Application:**

Screwjack assembly (lear model 504ac); t-37b acft

**Outer Member Outside Diameter:**

0.9360 inches

**Bore Center To Shank End Distance:**

Between 1.2400 inches and 1.2600 inches

**Inspection Hole Center To End Distance:**

0.3594 inches

**Shank Hole Length:**

0.6250 inches

**Thread Diameter:**

0.5000 inches

**Thready Qty Per Inch (tpi):**

20

**Product Name:**

Coupling driven end

**Special Features:**

Bearing p/n ksp3fs464 (nsn 3110-00-042-4804) is preinstalled into lug p/n 110660-05, cage 31435

**Material:**

Steel comp xm-13 rod end body

**Reference Data And Literature:**

T.O. 16g3-2-10-13

**Relationship To Similar Equipment:**

USAB-LE-INP-LACE

**Style Designator:**

Ball type

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0