NSN 3120-01-501-5352

Rod End Plain Bearing - Page 1 of 2

Thread Class:





3a
Thread Direction:
Right-hand
Shank Style:
Externally threaded
Overall Length:
2.8785 inches
Bore Diameter:
Between 0.3745 inches and 0.3750 inches
Outer Member Outside Diameter:
Between 1.1150 inches and 1.1350 inches
Bore Center To Shank End Distance:
Between 2.3020 inches and 2.3220 inches
Outer Member Width:
Between 0.3700 inches and 0.3750 inches
Inner Member Width:
Between 0.4980 inches and 0.5000 inches
Shank Thread Length:
Between 1.3440 inches and 1.4370 inches
Static Radial Load Rating:
15200 pounds
Thread Diameter:
0.438 inches
Thready Qty Per Inch (tpi):
20
Product Name:
Rod end
Special Features:
Self lubricated, salt water immersion; dyflon plastic alloy liner; the body, race and ball are stainless steel heat treated; low friction rod end
Material:
Stainless steel body
Style Designator:
Ball type extended one side
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 3120-01-501-5352

Rod End Plain Bearing - Page 2 of 2

Fiig: A045a0

