

View Online at <https://aerobasegroup.com/nsn/3120-01-527-5973>

**Overall Length:**

60.0 millimeters

**Body Outside Diameter:**

85.0 millimeters

**Body Inside Diameter:**

80.0 millimeters

**End Application:**

Steering group

**Special Features:**

Mat: permaglides p20 plain bearing material- contains lead, not for foodstuffs or pharmaceutical products; maximum pv value:  $pv \leq 3 \text{ n/mm}^2 \times \text{m/s}$ ; permissible specific bearing load: static-  $p_{max} \leq 250 \text{ n/mm}^2$ , permissible sliding speed  $v_{max} \leq 3 \text{ m/s}$ ; permissible operating temperature: continuous  $-40$  to  $+110$  c, short periods maximum  $+140$  c; inside of bearing is the lubrication pocket- deformation of lubrication chamfer and i hole due to round bending is permissible. One end of bearing sleeve seems tapered. The bearing is split and there is also a through hole in the side of the bearing measuring 6mm in width and bearing side thickness is 0.6mm

**Style Designator:**

17a-2 split, plain, no outside flanges, interior flang (s) not located at either end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A045a0