NSN 3120-01-560-5620

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-560-5620

| Overall Length: |
|---|
| 1.0800 inches |
| Body Outside Diameter: |
| Between 6.3422 inches and 6.3440 inches |
| Body Inside Diameter: |
| 5.5600 inches |
| Flange Outside Diameter: |
| 7.2500 inches |
| End Application: |
| C-135 aircraft |
| Flange Width: |
| Between 0.1650 inches and 0.1750 inches |
| Corner Shape: |
| Square outside left corner |
| Product Name: |
| Bushing - main landing gear, fwd trunnion |
| Material: |
| Copper alloy 630 or copper alloy 954 |
| Material Specification: |
| Mil-b-6946 cold drawn military specification single material response or qq-b-671. Class 3 federal specification single material response |
| Surface Treatment: |
| Cadmium right end surface of body or nickel right end surface of body and zinc right end surface of body |
| Surface Treatment Specification: |
| Ams-qq-pp-416 type ii, class (preferred) assn standard single treatment response left end surface of body and flange or ams 2417, type |
| or type 2 assn standard single treatment response left end surface of body and flange or ams 2451/4 or 3 assn standard single treatment |
| response left end surface of body and flange or ams 2451/9 type 1 or type 2 assn standard single treatment response left end surface of |
| body and flange |
| Style Designator: |
| 22c solid, external flange one end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A045a0 |
| Mil-std (military Standard): |
| Mil-b-6946 spec. |