NSN 3120-01-560-6640

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-560-6640

Overall Length:
1.0800 inches
Body Outside Diameter:
Between 6.3672 inches and 6.3693 inches
Body Inside Diameter:
5.5600 inches
Flange Outside Diameter:
7.2500 inches
End Application:
Kc-135 stratotanker bushing main landing gear; fwd trunnion
Flange Width:
Between 0.1650 inches and 0.1750 inches
Corner Shape:
Square outside left corner
Surface Finish:
63.0 microinches left end surface of body and flange
Product Name:
Bushing-aft 2nd over
Material:
Copper alloy 630 or copper alloy 954 or copper alloy 955
Material Specification:
Mil-b-6946 cold drawn military specification single material response or qq-b-671 class 3 ht tr federal specification single material response
or qq-b-671 class 4 ht tr federal specification single material response
Surface Treatment:
Cadmium right end surface of left flange or zinc right end surface of left flange and nickel right end surface of left flange
Surface Treatment Specification:
Ams-qq-pp-416 type 2 class 3 assn standard single treatment response right end surface of left flange or ams2417 type 1 or type 2 assn
standard single treatment response right end surface of left flange or ams2451/4 or 3 assn standard single treatment response right end
surface of left flange or ams 2451/9 type 1 or type 2 assn standard single treatment response right end surface of left flange
Style Designator:
22c solid, external flange one end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A045a0
Mil-std (military Standard):
Mil-b-6946 spec.