NSN 3120-01-560-6661

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-560-6661

| View Online at https://aerobasegroup.com/nsn/3120-01-560-6661 |
|---|
| Overall Length: |
| 1.0800 inches |
| Body Outside Diameter: |
| Between 6.3572 inches and 6.3593 inches |
| Body Inside Diameter: |
| 5.5600 inches |
| Flange Outside Diameter: |
| 7.2500 inches |
| End Application: |
| C-135 aircraft; bushing-main landing gear, fwd trunnion |
| Flange Width: |
| Between 0.1650 inches and 0.1750 inches |
| Surface Finish: |
| 63.0 microinches inside diameter surface of body |
| Product Name: |
| Bushing fwd 1st over |
| Material: |
| Copper alloy 630 or copper alloy 954 or copper alloy 955 |
| Material Specification: |
| Mil-b-6946 cold drawn military specification single material response or qq-b-671, class 3 ht tr federal specification single material response |
| or qq-b-671 class 4 ht tr federal specification single material response |
| Surface Treatment: |
| Cadmium right end surface of left flange or zinc right end surface of left flange and nickel right end surface of left flange |
| Surface Treatment Specification: |
| Ams-aa-99-416, type ii, class (preferred) assn standard single treatment response left end surface of body and flange or ams 2417, type |
| 1 or type 2 assn standard single treatment response left end surface of body and flange or ams 2451/4 or 3 assn standard single treatment |
| response left end surface of body and flange or ams 2451/9, type 1 or type 2 assn standard single treatment response left end surface of |
| body and flange |
| Style Designator: |
| 22c solid, external flange one end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A045a0 |
| Mil-std (military Standard): |

Mil-b-6946 spec.