Rod End Plain Bearing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-603-7974

Right-hand         Shink Style:         Extemply threaded         Born Dimeter:         0.2500 inches         Outer Member Outside Diameter:         0.2500 inches         Born Distance:         0.4320 inches         Borne Member Outside Diameter:         0.4398 inches         Borne Member Width:         0.5312 inches         Shank Thread Length:         1.4370 inches         Thread Diameter:         0.3500 inches         Thread Very Per Inch (ptp):         20.300 inches         20.3750 inches         Thread Stating:         0.3750 inches         Baterial:         Storokeult in inner member         Storokeult inner	Thread Direction:	
Externally threaded   Bore Diameter:   0.2500 inches   Outer Member Outside Diameter:   0.6250 inches   Bore Center To Shank End Distance:   2.4398 inches   Inner Member Width:   0.5312 inches   Shank Thread Length:   1.1870 inches   Chread Ver Per Inch (pi):   203ajda3b   Hardness Rating:   3.7.0 rockwell c inner member   Material:   Stor Source Sourc	Right-hand	
Bore Diameter: 0.2500 inches 0.2500 inches 0.2500 inches 0.2500 inches 0.2500 inches Bore Center To Shank End Distance: 2.4398 inches 2.4398 inches 0.3512 inches 0.3512 inches 0.3512 inches 0.3512 inches 0.3512 inches 0.3510 i	Shank Style:	
0.2500 inches Outer Member Outside Diameter: 0.6250 inches Bore Center To Shank End Distance: 2.4398 inches Inner Member Width: 0.5312 inches Oshank Thread Length: 1.1870 inches Thread Diameter: 0.3750 inches Thread Diameter: 0.3750 inches Thread Qi YPer Inch (tpi): 20aajda3b Hardness Rating: 37.0 rockwell c inner member Material: Steel comp xm-12 or steel comp 630 body Material: Steel comp xm-12 or steel comp 630 body Material Specification: Ams 5659 assn standard single material response or ams 5343 assn standard single material response or ams 5355 assn standard single material response body Style Designator: Ball type Thread Series Designator: Unif Sheft Life: Na	Externally threaded	
Outer Member Outside Diameter:         0.6250 inches         Bore Center To Shank End Distance:         2.4398 inches         Inner Member Width:         0.5312 inches         Shank Thread Length:         1.1870 inches         Thread Diameter:         0.3750 inches         Thread Quy Per Inch (tpl):         20aajda3b         Hardness Rating:         37.0 rockwell c inner member         Material:         Stel comp xm-12 or stel comp 630 body         Material:         Syle Designator:         Ball type         Syle Designator:         Ball type         Thread Series Designator:         Unif         Shelf Life:         Na	Bore Diameter:	
0.5250 inches Bore Center To Shank End Distance: 2.4398 inches Inner Member Width: 0.5312 inches Shank Thread Length: 1.1870 inches Thread Diameter: 0.3750 inches Thread Y Per Inch (tpi): 20agida3b Hardness Rating: 37.0 rockwell c inner member Material: Steel comp xm-12 or steel comp 630 body Material Specification: Ams 5659 assn standard single material response or ams 5343 assn standard single material response or ams 5355 assn standard single material response body Style Designator: Ball type Thread Series Designator: Unjf Shelf Life: Na	0.2500 inches	
Bore Center To Shank End Distance: 2.4398 inches Inner Member Width: 0.5312 inches Shank Thread Length: 1.1870 inches Thread Diameter: 0.3750 inches Thread Vid Per Inch (tpi): 0.3750 inches Thread Yie Pr Inch (tpi): 0.370 inches Thread Stating: 37.0 rockwell c inner member Material: Steel comp xm-12 or steel comp 630 body Material Specification: Ams 5659 assn standard single material response or ams 5343 assn standard single material response or ams 5355 assn standard single material response o	Outer Member Outside Diameter:	
2.4398 inches iner Member Width: 0.5312 inches Shank Thread Length: 1.1870 inches Thread Diameter: 0.3750 inches Thread Diameter: 0.3750 inches Thread Qty Per Inch (tpi): 20aajda3b Hardness Rating: 37.0 rockwell c inner member Material: Steel comp xm-12 or steel comp 630 body Material Specification: Ams 5659 assn standard single material response or ams 5343 assn standard single material response or ams 5355 assn standard single material response body Style Designator: Ball type Thread Series Designator: Unjf Shelf Lifte: Na	0.6250 inches	
Iner Member Width: 0.5312 inches Shank Thread Length: 1.1870 inches Thread Diameter: 0.3750 inches Thread Vay Per Inch (tpi): 20aajda3b Hardness Rating: 37.0 rockwell c inner member Material: Steel comp xm-12 or steel comp 630 body Material Specification: Ams 5659 assn standard single material response or ams 5343 assn standard single material response or ams 5355 assn standard sin material response body Style Designator: Ball type Thread Series Designator: Unjf Shelf Life: Na Ma	Bore Center To Shank End Distance:	
0.5312 inches Shank Thread Length: 1.1870 inches Thread Diameter: 0.3750 inches Thready Qty Per Inch (tpi): 20aajda3b Hardness Rating: 37.0 rockwell c inner member Material: Steel comp xm-12 or steel comp 630 body Material Specification: Ams fo59 assn standard single material response or ams 5343 assn standard single material response or ams 5355 assn standard sin material response body Style Designator: Ball type Thread Series Designator: Unjf Shef Life: N/a	2.4398 inches	
Shank Thread Length:   1.1870 inches   Thread Diameter:   0.3750 inches   Thread Qty Per Inch (tpi):   20aajda3b   Hardness Rating:   37.0 rockwell c inner member   Material:   Steel comp xm-12 or steel comp 630 body   Material Specification:   Ams 5659 assn standard single material response or ams 5343 assn standard single material response or ams 5355 assn standard single material response body   Style Designator:   Ball type   Thread Series Designator:   Unjf   Sheft Life:   N/a   Unjf   Sheft Life:   N/a	Inner Member Width:	
1.1870 inches Thread Diameter: 0.3750 inches Thready Qty Per Inch (tpi): 20aajda3b Hardness Rating: 37.0 rockwell c inner member Material: Steel comp xm-12 or steel comp 630 body Material Specification: Ams 5659 assn standard single material response or ams 5343 assn standard single material response or ams 5355 assn standard sing material response body Style Designator: Ball type Thread Series Designator: Unjf Shelf Life: N/a	0.5312 inches	
Thread Diameter: 0.3750 inches Thready Qty Per Inch (tpi): 20aajda3b Hardness Rating: 37.0 rockwell c inner member Material: Steel comp xm-12 or steel comp 630 body Material Specification: Ams 5659 assn standard single material response or ams 5343 assn standard single material response or ams 5355 assn standard sin material response body Style Designator: Ball type Thread Series Designator: Unjf Shelf Life: N/a	Shank Thread Length:	
0.3750 inches Thready Qty Per Inch (tpi): 20ajda3b Hardness Rating: 37.0 rockwell c inner member Material: Steel comp xm-12 or steel comp 630 body Material Specification: Ams 5659 assn standard single material response or ams 5343 assn standard single material response or ams 5355 assn standard sin material response body Style Designator: Ball type Thread Series Designator: Unjf Shelf Life: N/a	1.1870 inches	
Thready Qty Per Inch (tpi): 20aajda3b Hardness Rating: 37.0 rockwell c inner member Material: Steel comp xm-12 or steel comp 630 body Material Specification: Ams 5659 assn standard single material response or ams 5343 assn standard single material response or ams 5355 assn standard sin material response body Style Designator: Ball type Thread Series Designator: Unjf Shelf Life: N/a	Thread Diameter:	
20aajda3b Hardness Rating: 37.0 rockwell c inner member Material: Steel comp xm-12 or steel comp 630 body Material Specification: Ams 5659 assn standard single material response or ams 5343 assn standard single material response or ams 5355 assn standard sin material response body Style Designator: Ball type Thread Series Designator: Unjf Shelf Life: N/a Unit of Measure:	0.3750 inches	
Hardness Rating:         37.0 rockwell c inner member         Material:         Steel comp xm-12 or steel comp 630 body         Material Specification:         Ams 5659 assn standard single material response or ams 5343 assn standard single material response or ams 5355 assn standard single material response body         Style Designator:         Ball type         Thread Series Designator:         Unjf         Shelf Life:         N/a	Thready Qty Per Inch (tpi):	
37.0 rockwell c inner member Material: Steel comp xm-12 or steel comp 630 body Material Specification: Ams 5659 assn standard single material response or ams 5343 assn standard single material response or ams 5355 assn standard sin material response body Style Designator: Ball type Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure:	20aajda3b	
Material:   Steel comp xm-12 or steel comp 630 body   Material Specification:   Ams 5659 assn standard single material response or ams 5343 assn standard single material response or ams 5355 assn standard single material response body   Style Designator:   Ball type   Thread Series Designator:   Unjf   Shelf Life:   N/a   Unit Of Measure:	Hardness Rating:	
Steel comp xm-12 or steel comp 630 body Material Specification: Ams 5659 assn standard single material response or ams 5343 assn standard single material response or ams 5355 assn standard sin material response body Style Designator: Ball type Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure:	37.0 rockwell c inner member	
Material Specification:         Ams 5659 assn standard single material response or ams 5343 assn standard single material response or ams 5355 assn standard single material response or ams 5343 assn standard single material response or ams 5355 assn stand	Material:	
Ams 5659 assn standard single material response or ams 5343 assn standard single material response or ams 5355 assn standard sin material response body Style Designator: Ball type Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure:	Steel comp xm-12 or steel comp 630 body	
material response body Style Designator: Ball type Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure:	Material Specification:	
Style Designator:   Ball type   Thread Series Designator:   Unjf   Shelf Life:   N/a   Unit Of Measure:	Ams 5659 assn standard single material response	or ams 5343 assn standard single material response or ams 5355 assn standard single
Ball type Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure:	material response body	
Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure:	Style Designator:	
Unjf Shelf Life: N/a Unit Of Measure:	Ball type	
Shelf Life: N/a Unit Of Measure:	Thread Series Designator:	
N/a Unit Of Measure:	Unjf	
Unit Of Measure:	Shelf Life:	
	Unit Of Measure:	
Demilitarization:		
No		
Fiig: A045a0		