NSN 3120-01-625-1943

Sleeve Bushing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3120-01-625-1943

Overal	م ا اا	natk	١.
Overa	II LC	HULL	ı.

Between 0.295 inches and 0.300 inches

Body Outside Diameter:

Between 0.3756 inches and 0.3761 inches

Body Inside Diameter:

Between 0.2380 inches and 0.2430 inches

Flange Outside Diameter:

Between 0.427 inches and 0.447 inches

End Application:

Stand assembly/control instl - catain's and first officer stab trim

Flange Width:

Between 0.055 inches and 0.060 inches

Hardness Rating:

50.0 rockwell r

Surface Finish:

63.0 microinches outside diameter surface of body

Product Name:

Bushing, flanged, press fit, undersize inside diameter

Special Features:

Chamfer all corners iaw nas538

Material:

Bronze aluminum outside diameter surface of body

Material Specification:

Astm b150/b150m or ams4640 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams-qq-p-416, ty ii, cl 2 assn standard single treatment response

Style Designator:

Solid, external flange one end

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

Fiig:

A045a0