

View Online at <https://aerobasegroup.com/nsn/3120-01-628-8836>

Thread Class:

3a

Thread Direction:

Left-hand

Shank Style:

Externally threaded

Overall Length:

2.595 inches

Bore Diameter:

Between 0.3745 inches and 0.3750 inches

Outer Member Outside Diameter:

Between 1.121 inches and 1.141 inches

Bore Center To Shank End Distance:

Between 2.020 inches and 2.040 inches

Outer Member Width:

Between 0.3170 inches and 0.3270 inches

Inner Member Width:

Between 0.4040 inches and 0.4060 inches

Shank Thread Length:

Between 1.156 inches and 1.218 inches

Static Radial Load Rating:

13000 pounds

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

55.0 rockwell c and 62.0 rockwell c inner member

Lubrication Feature:

Self-lubricating liner internal outer member

Special Features:

Key way in shank

Material:

Steel comp e4340 rod end body

Material Specification:

Ams 5630 assn standard single material response inner member

Surface Treatment:

Cadmium rod end body

Surface Treatment Specification:

Qq-p-416, type 2, class2 federal specification single treatment response rod end body

Style Designator:

Ball type

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A045a0

Mil-std (military Standard):

Mil-s-5000 spec.