

View Online at <https://aerobasegroup.com/nsn/3130-00-121-6426>

**End Application:**

Bell helicopter model oh-58

**General Description:**

Steel, corrosion resisting, comp 17-4ph and plastic tetrafluorethylene bore liner, bearing dim., 0.375 in. Nom o/a lg, 1.200 in. Nom flange lg by 0.873 in. Nom flange width, 0.260 in. Nom flange thk at base, 0.100 in. Nom flange thk at top, 0.615 in. Min, 0.625 in. Maximum od, 0.4385 in. Min, 0.4395 in. Maximum id of polytetrafluoroethylene liner, 0.625 in. Counterbore id by 0.075 in. Deep on flange side, right face of flange rounded by 1.960 in. Min, 1.970 in. Maximum spherical radius, left face is tapered by 15.0 degrees angle, bushing sleeve dim., 0.3715 in. Min, 0.3775 in. Maximum o/a lg, 0.0615 in. Min, 0.0625 in. Maximum flange thk, 0.550 in. Min, 0.560 in. Maximum flange od, 0.4375 in. Nom body od, 0.3120 in. Min, 0.3125 in. Maximum body id

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli