

View Online at <https://aerobasegroup.com/nsn/3130-00-689-6318>

**General Description:**

Cres ams5643 17-4ph, cadmium plated class 2 type 2 per bps-fw-4006 fscm97499 od of right external flange left end surface of right external flange and body od, passivate per bps-fw-4007 fscm 97499 o/a, 1.155 in. Min 1.175 in. Max body id, 1.377 in. Min 1.378 in. Maximum body od, 0.878 in. Min 0.880 in. Max o/a lg, 1.740 in. Min 1.760 in. Maximum right external flange od, 0.064 in. Min 0.066 in. Maximum right external flange w, 0.906 in. Min 0.916 in. Maximum left internal flange hole dia, 0.058 in. Min 0.080 in. Maximum left internal flange w, 2 slots 180 degrees apart in left internal flange, 0.115 in. Min 0.130 in. Max depth of slot, 0.115 in. Min 0.135 in. Maximum w of slots, 2 grooves in id, one groove located 0.300 in. Min 0.320 in. Maximum from right external flange, 0.180 in. Min 0.200 in. Maximum w, 0.0225 in. Min 0.0425 in. Maximum depth, other groove located 0.730 in. Min 0.770 in. Maximum from right external flange, 0.050 in. Min 0.070 in. Maximum w, 0.0225 in. Min 0.0425 in. Maximum depth, 2 holes through body located 0.395 in. Min 0.415 in. Maximum fr

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A23900