

View Online at <https://aerobasegroup.com/nsn/3130-00-707-3533>

General Description:

Steel, mil-s-6758 comp 4130 condition d4 or steel, mil-s-5626 comp 4140condition c4, 1 7/16 in. Flange od, 1.2515 in. Min 1.2520 in. Maximum body od, 1.083 in. Min 1.103 in. Maximum body id, 0.090 in. Min 0.100 in. Maximum rightinternal flange w, 0.990 in. Min 1.010 in. Maximum right internal flange holedia, inside left corner chamfered 0.025 in. Min 0.035 in. Maximum dia, 45 degangle, outside right corner chamfered 0.005 in. Min 0.015 in. Maximum dia, 45deg angle, 0.015 in. Min 0.020 in. Maximum depth, 0.062 in. Maximum w left flangebody corner, keyway 0.125 in. W, 0.021 in. Depth spaced 180 degrees apart inright internal flange, 0.062 in. Keyway lg, 125 microinches left and rightside, od of left external flange and right side of right internal flange, all other surfaces 63 microinches aa, all surfaces cadmium plated cl 2type 2 bps fw 4006 fscm 97499 except id, right and left side of rightinternal flange must be parallel to right and left side of left externalflange and sq with id and od within 0.0005 in. Tir, id and od of body and

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23900