

View Online at <https://aerobasegroup.com/nsn/3130-00-707-3534>

General Description:

Steel, mil-s-6758 comp 4130 condition d4 or steel mil-s-5626 comp 4140condition c4, 1 3/16 in. Flange od, 1.0010 in. Min 1.0015 in. Maximum body od, 0.8740 in. Min 0.8745 in. Maximum body id, 0.052 in. Min 0.072 in. Maximum rightinternal flange w, 0.802 in. Min 0.822 in. Maximum right internal flange holedia, 0.875 in. Min 0.885 in. Maximum right internal flange body corner dia, 0.060 in. W, 0.015 in. Corner radius, inside left corner chamfered 0.025in. Min 0.035 in. Maximum dia, 45 degrees angle, outside right corner chamfered0.005 in. Min 0.015 in. Maximum dia, 45 degrees angle, 0.015 in. Min 0.020 in. Maxdepth, 0.062 in. Maximum w left flange body corner, keyway 0.125 in. W 0.021in. Depth spaced 180 degrees apart in right internal flange, 0.062 in. Keywaylg, 125 microinches left and right side, od of left external flange andright side of right internal flange, all other surfaces 63 microinches aa, right side of left external flange 0.186 in. Min 0.188 in. Maximum from leftside internal flange, all surfaces cadmium plated, cl 2 type 2 bps fw 4

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23900