NSN 3130-00-735-2183

Ball Bearing Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3130-00-735-2183

| Mounting Hole Diameter: |
|---|
| 0.4844 inches |
| Bore Diameter: |
| 0.5000 inches |
| Base Thickness: |
| 0.6250 inches |
| Center To Center Distance Between Mounting Holes Along Width: |
| 3.1250 inches |
| Housing Height: |
| 2.1250 inches |
| Housing Width: |
| 4.2500 inches |
| Lubrication Fitting Type: |
| Pipe plug |
| Base Length: |
| 1.0625 inches |
| Rolling Element Groove Quantity: |
| 1 |
| Alignment Type: |
| Rigid |
| Internal Fit-up Designation: |
| Standard |
| Assemblylength: |
| 1.4219 inches |
| Seal Type: |
| Contact |
| Block Type: |
| Fixed |
| Shaft End Type: |
| Open |
| Seal Location: |
| Both ends |
| Collar Location: |
| One end |
| Load Capability Type: |
| Radial |
| Height From Bottom Of Base To Bore Centerline: |
| 1.0625 inches |
| Features Provided: |
| Ground rolling element groove |

90.0 degrees

Lubrication Fitting Angle From Horizontal Centerline:

NSN 3130-00-735-2183

Ball Bearing Unit - Page 2 of 2



Rotating Element Locking Method: Eccentric cam locking collar **Lubrication Material:** Grease Material: Steel seal and rubber synthetic seal Style Designator: Pillow block, solid Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

Fiig:

A093a0