

View Online at <https://aerobasegroup.com/nsn/3130-00-830-4285>

General Description:

Steel mil-s-6758 comp 4130 cond d1 or mil-s-5626 comp 4140 or ams 6415comp 4340 or mil-t-6736 comp 4130 type 1 cond n or ams 6381 comp 4140, blackoxide per bps fw 4084 fscm 97499, dim., 2.230 in. Min 2.250 in. Maximum right internal flange hole dia, 0.110 in. Min 0.133 in. Maximum right internal flange w, 1.730 in. Min 1.754 in. Maximum o/a lg, 2.415 in. Min 2.420 in. Maximum id, 2.616 in. Min 2.617 in. Maximum od, 2.880 in. Min 2.900 in. Maximum left flange od, 0.100 in. Min 0.104 in. Maximum left flange w, right outside corner and left flange outside right corner chamfered 0.030 in. By 45 deg, left flange body corner and right internal flange id corner round 0.020 in. Radius, 3 holes drilled at 30 degrees angle through body, 0.077 in. Min 0.082 in. Maximum hole dia, holes located 0.40 in. Min 0.46 in. Maximum from right end surface of body, 63 microinches aa od, all other surfaces 125 microinches aa, magnetic particle inspected per mil-i-6868 and bps 4075 fscm 97499, od and right end surface of left flange sq within 0.002 in. Tir

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23900