## NSN 3130-00-880-2232

Plain Bearing Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3130-00-880-2232

Mounting Slot Width:
0.400 inches
Mounting Slot Length:
0.650 inches
Bore Diameter:
Between 1.0010 inches and 1.0020 inches
Base Thickness:
0.190 inches
Center To Center Distance Between Mounting Holes Along Width:
2.970 inches
Housing Height:
1.810 inches
Housing Length:
1.130 inches
Housing Width:
4.030 inches
Lubrication Fitting Type:
Cup
Base Length:
1.130 inches
Alignment Type:
Rigid
Assemblylength:
1.250 inches
Shaft End Type:
Open
Load Capability Type:
Radial
Height From Bottom Of Base To Bore Centerline:
0.940 inches
Lubrication Fitting Angle From Horizontal Centerline:
45.0 degrees
Mounting Hole Type:
Slotted
Lubrication Material:
Oil
Material:
Steel outer ring
Material Specification:
Qq-s-698 federal specification single material response outer ring
Surface Treatment:

Enamel housing

## NSN 3130-00-880-2232

Plain Bearing Unit - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Tt-e-529 federal specification single treatment response housing

**Style Designator:** 

Pillow block, separable w/o innerliner

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A093a0

Mil-std (military Standard):

Mil-b-5687 spec.