

View Online at <https://aerobasegroup.com/nsn/3130-00-917-7069>

General Description:

Cres, ams 5643 comp 17-4ph, passivated fw 4007 bell helicopter co o/cadmium-plated qq-p-416 od and right hand surface of left flange, dim., 1.330in. Min, 1.340 in. Maximum id, 1.502 in. Min, 1.503 in. Maximum od, 4.085 in. Min, 4.095in. Maximum o/a lg, 1.740 in. Min, 1.760 in. Maximum flange od, 0.060 in. Min, 0.065 in. Max flange w, 0.890 in. Min, 0.910 in. Maximum internal flange dia, 0.115 in. Min, 0.135 in. Maximum internal flange w, internal flange corner grooved 0.125 in. Nomw by 1.400 in. Min, 1.410 in. Maximum dia, inside left corner chamfered 0.060 in. Nom lg by 30 deg, left flange body corner rounded 0.060 in. Min, 0.070 in. Maxradius, outside right corner chamfered 0.060 in. Nom by 15 deg, max surfacefinish, all surfaces 63 microinches aa, all diameters concentric within 0.003tir, fluorescent penetrant inspected fw 4089 bell helicopter co

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23900