NSN 3130-00-967-2840

Ball Bearing Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3130-00-967-2840

Mounting Hole Diameter: 0.5625 inches Bore Diameter: 1.8250 inches Housing Length: 1.5625 inches Housing Width: 5.3750 inches Lubrication Fitting Type: Hydraulic Rolling Element Groove Quantity: 1 Alignment Type: Self-aligning Internal Fit-up Designation: Standard Assemblylength: 2.0468 inches Self-aligning Block Type: Fixed Standard Assemblylength: 2.0468 inches Seal Type: Singer Block Type: Fixed Standard August Jopen Sel Location: One end Collar Location: One end Fatures Provided: Ground rolling element groove Lubrication Fitting Angle From Horizontal Centerline: 90.0 degrees Grease Material: Steel seal and woo		
Bore Diameter: 1.6250 inches Housing Length: 1.6250 inches Housing Width: 5.3750 inches Lubrication Fitting Type: Hydraulic Rolling Element Groove Quantity: 1 Alignment Type: Self-aligning Internal Fit-up Designation: Standard Assemblylength: 2.0468 inches Seal Type: Slinger Block Type: Fiked Standard Assemblylength: 2.0468 inches Seal Type: Slinger Block Type: Open Seal Location: Open Seal Location: One end Fotures Provided: Ground filling element groove Lubrication Fitting Angle From Horizontal Centerline: 9.0.0 degrees Rating Element Locking Method: Setsorew locking collar Lubrication Material: Setsorew locking collar Lubrication Material: Seto	Μ	lounting Hole Diameter:
1.8250 inches Housing Width: 1.5625 inches Housing Width: 5.3750 inches Lubrication Fitting Type: Hydraulic Rolling Element Groove Quantity: 1 Alignment Type: Self-aligning Internal Fit-up Designation: Standard Assemblylength: 2.0468 inches Self self self and (Context) Standard Assemblylength: 2.0468 inches Self self self self self self self self s		
Housing Width: 1.5625 inches Housing Width: 5.3750 inches Lubrication Fitting Type: Hydraulic Rolling Element Groove Quantity: 1 Alignment Type: Self-aligning Internal Fit-up Designation: Standard Assemblylength: 2.0468 inches Seal Type: Solaf Type: Silloger Block Type: Fixed Shaft End Type: Open Seal Location: One end Collar Location: Ground rolling element groove Lubrication Fitting Angle From Horizontal Centerline: 90.0 degrees Rotating Element Locking Method: Stesrew locking collar Lubrication Material: Stesrew locking collar Lubrication Material: Stesrew locking collar Lubrication Material: Stesrew locking collar	В	ore Diameter:
1.5625 inches Housing Width: 5.3750 inches Lubrication Fitting Type: Hydraulic Rolling Element Groove Quantity: 1 Alignment Type: Self-aligning Internal Fit-up Designation: Standard Assemblylength: 2.0468 inches Seal Type: Slinger Block Type: Skinger Boat End Type: Open Shaft End Type: Open Seal Cootion: One end Features Provided: Ground rolling element groove Lubrication Fitting Angle From Horizontal Centerline: 90.0 digrees Rotating Element Locking Method: Setersev locking collar Lubrication Material: Greese Material: Steel seal and wool seal	1.	6250 inches
Housing Width: 5.3750 Inches Lubrication Fitting Type: Hydraulic Rolling Element Groove Quantity: 1 Jagment Type: Self-aligning Internal Fit-up Designation: Standard Assemblylength: 2.0468 Inches Self-aligning Bock Type: Slinger Block Type: Fixed Shaft End Type: Open Self-aligning in: Open Ground rolling element groove Lubrication: One end Fixed Fortures Provided: Ground rolling element groove Lubrication Fitting Angle From Horizontal Centerline: 90.0 degrees Rotating Element Locking Method: Setersev locking colar Lubrication Material: Grease Material: Seterse and wool seal	н	ousing Length:
S.3750 inches Lubrication Fitting Type: Hydraulic Rolling Element Groove Quantity: 1 Alignment Type: Self-aligning Internal Fit-up Designation: Standard Assemblylength: 2.0468 inches Self-aligning Block Type: Slinger Block Type: Fixed Shaft End Type: Open Seal Location: One end Collar Location: Ground rolling element groove Lubrication Fitting Angle From Horizontal Centerline: 9.0 degrees Rotating Element Locking Method: Grease Material: Stel seal and wool seal	1.	5625 inches
Lubrication Fitting Type: Hydraulic Rolling Element Groove Quantity: 1 Alignment Type: Self-aligning Internal Fit-up Designation: Standard Assemblylength: 2.0468 inches Seal Type: Silnger Block Type: Fixed Staft End Type: Open Seal Location: One end Collar Location: One end Foruer Tritting Angle From Horizontal Centerline: 90.0 degrees Rotating Element Locking Method: Stesrew locking collar Lubrication Material: Grease Material: Stesreal and wool seal	н	ousing Width:
Hydraulic Rolling Element Groove Quantity: 1 Alignment Type: Self-aligning Internal Fit-up Designation: Standard Assemblylength: 2.0468 inches Seal Type: Slinger Block Type: Fixed Standard O Seal Type: Slinger Block Type: Fixed Standard O Seal Coation: Open Seal Location: One end Fetures Provided: Ground rolling element groove Lubrication Fitting Angle From Horizontal Centerline: 9.0 degrees Rotating Element Locking Method: Stescrew locking collar Lubrication Material: Grease Material: Steel seal and wool seal	5.	.3750 inches
Rolling Element Groove Quantity: 1 Alignment Type: Self-aligning Internal Fit-up Designation: Standard Assemblylength: 2.0468 inches Seal Type: Slinger Block Type: Fixed Shaft End Type: Open Seal Location: One end Fatures Provided: Ground rolling element groove Lubrication Fitting Angle From Horizontal Centerline: 9.0.0 degrees Rotating Element Locking Method: Grease Material: Steel seal and wool seal	L	ubrication Fitting Type:
1 Alignment Type: Self-aligning Internal Fit-up Designation: Standard Assemblylength: 2.0468 inches Seal Type: Slinger Block Type: Fixed Shaft End Type: Open Seal Location: One end Fatures Provided: Ground rolling element groove Lubrication Fitting Angle From Horizontal Centerline: 90.0 degrees Rotating Element Locking Method: Setscrew locking collar Lubrication Material: Grease Material: Steel seal and wool seal	Н	ydraulic
Alignment Type:Self-aligningInternal Fit-up Designation:StandardAssemblylength:2.0468 inchesSeal Type:SlingerBlock Type:FixedShaft End Type:OpenSeal Location:One endCollar Location:One endFactures Provided:Ground rolling element grooveLubrication Fitting Angle From Horizontal Centerline:9.0 degreesRotting Element Locking Method:Setscrew locking collarLubrication Material:GreaseMaterial:Steel seal and wool seal	R	olling Element Groove Quantity:
Sdf-aligning Internal Fit-up Designation: Standard Assemblylength: 2.0468 inches Seal Type: 2.0468 inches Seal Type: Slinger Block Type: Fixed Shaft End Type: Fixed Shaft End Type: Open Seal Location: One end Collar Location: One end Features Provided: Ground rolling element groove Lubrication Fitting Angle From Horizontal Centerline: 90.0 degrees Rotating Element Locking Method: Setscrew locking collar Lubrication Material: Grease Material: Steel seal and wool seal	1	
Internal Fit-up Designation: Standard Assemblylength: 2.0468 inches Seal Type: Slinger Block Type: Fixed Shaft End Type: Open Seal Location: One end Fore and Fore and Ground rolling element groove Lubrication Fitting Angle From Horizontal Centerline: 90.0 degrees Rotating Element Locking Method: Stescrew locking collar Lubrication Material: Grease Material: Stescrew locking collar	Α	lignment Type:
Standard Assemblylength: 2.0468 inches Seal Type: Slinger Block Type: Fixed Shaft End Type: Open Seal Location: One end Collar Location: One end Features Provided: Ground rolling element groove Lubrication Fitting Angle From Horizontal Centerline: 90.0 degrees Rotating Element Locking Method: Setscrew locking collar Lubrication Material: Grease Material: Steel seal and wool seal	S	elf-aligning
Assemblylength:2.0468 inchesSeal Type:SlingerBlock Type:FixedShaft End Type:OpenSeal Location:One endCollar Location:One endFeatures Provided:Ground rolling element grooveLubrication Fitting Angle From Horizontal Centerline:90.0 degreesRotating Celement Locking Method:Setscrew locking collarLubrication Material:GreaseMaterial:Stel seal and wool seal	In	ternal Fit-up Designation:
2.0488 inches Seal Type: Slinger Block Type: Fixed Shaft End Type: Open Seal Location: One end Collar Location: One end Features Provided: Ground rolling element groove Lubrication Fitting Angle From Horizontal Centerline: 90.0 degrees Rotating Element Locking Method: Setscrew locking collar Lubrication Material: Grease Material: Steel seal and wool seal	S	tandard
Seal Type:SlingerBlock Type:FixedShaft End Type:OpenSeal Location:One endCollar Location:One endFeatures Provided:Ground rolling element grooveLubrication Fitting Angle From Horizontal Centerline:90.0 degreesRotating Element Locking Method:Setscrew locking collarLubrication Material:GreaseMaterial:Steel seal and wool seal	Α	ssemblylength:
SlingerBlock Type:FixedShaft End Type:OpenSeal Location:One endCollar Location:One endFeatures Provided:Ground rolling element grooveLubrication Fitting Angle From Horizontal Centerline:90.0 degreesRotating Element Locking Method:Setscrew locking collarLubrication Material:GreaseMaterial:Stel seal and wool seal	2.	.0468 inches
Biock Type:FixedShaft End Type:OpenSeal Location:One endCollar Location:One endFeatures Provided:Ground rolling element grooveLubrication Fitting Angle From Horizontal Centerline:90.0 degreesRotating Element Locking Method:Setscrew locking collarLubrication Material:GreaseMaterial:Steel seal and wool seal	S	eal Type:
FixedShaft End Type:OpenSeal Location:One endCollar Location:One endFeatures Provided:Ground rolling element grooveLubrication Fitting Angle From Horizontal Centerline:90.0 degreesRotating Element Locking Method:Setscrew locking collarLubrication Material:GreaseMaterial:Steel seal and wool seal	S	linger
Shaft End Type:OpenSeal Location:One endCollar Location:One endFeatures Provided:Ground rolling element grooveLubrication Fitting Angle From Horizontal Centerline:90.0 degreesRotating Element Locking Method:Setscrew locking collarLubrication Material:GreaseMaterial:Steel seal and wool seal	В	lock Type:
OpenSeal Location:One endCollar Location:One endFeatures Provided:Ground rolling element grooveLubrication Fitting Angle From Horizontal Centerline:90.0 degreesRotating Element Locking Method:Setscrew locking collarLubrication Material:GreaseMaterial:Steel seal and wool seal	Fi	ixed
Seal Location:One endCollar Location:One endFeatures Provided:Ground rolling element grooveLubrication Fitting Angle From Horizontal Centerline:90.0 degreesRotating Element Locking Method:Setscrew locking collarLubrication Material:GreaseMaterial:Steel seal and wool seal	S	haft End Type:
One endCollar Location:One endFeatures Provided:Ground rolling element grooveLubrication Fitting Angle From Horizontal Centerline:90.0 degreesRotating Element Locking Method:Setscrew locking collarLubrication Material:GreaseMaterial:Steel seal and wool seal	0	pen
Collar Location:One endFeatures Provided:Ground rolling element grooveLubrication Fitting Angle From Horizontal Centerline:90.0 degreesRotating Element Locking Method:Setscrew locking collarLubrication Material:GreaseMaterial:Steel seal and wool seal	S	eal Location:
One endFeatures Provided:Ground rolling element grooveLubrication Fitting Angle From Horizontal Centerline:90.0 degreesRotating Element Locking Method:Setscrew locking collarLubrication Material:GreaseMaterial:Steel seal and wool seal	0	ine end
Features Provided:Ground rolling element grooveLubrication Fitting Angle From Horizontal Centerline:90.0 degreesRotating Element Locking Method:Setscrew locking collarLubrication Material:GreaseMaterial:Steel seal and wool seal	С	ollar Location:
Ground rolling element grooveLubrication Fitting Angle From Horizontal Centerline:90.0 degreesRotating Element Locking Method:Setscrew locking collarLubrication Material:GreaseMaterial:Steel seal and wool seal	0	ine end
Lubrication Fitting Angle From Horizontal Centerline: 90.0 degrees Rotating Element Locking Method: Setscrew locking collar Lubrication Material: Grease Material: Steel seal and wool seal	F	eatures Provided:
90.0 degrees Rotating Element Locking Method: Setscrew locking collar Lubrication Material: Grease Material: Steel seal and wool seal	G	round rolling element groove
Rotating Element Locking Method: Setscrew locking collar Lubrication Material: Grease Material: Steel seal and wool seal	L	ubrication Fitting Angle From Horizontal Centerline:
Setscrew locking collar Lubrication Material: Grease Material: Steel seal and wool seal	9(0.0 degrees
Lubrication Material: Grease Material: Steel seal and wool seal	R	otating Element Locking Method:
Grease Material: Steel seal and wool seal	S	etscrew locking collar
Material: Steel seal and wool seal	Ľ	ubrication Material:
Steel seal and wool seal	G	rease
	Μ	laterial:
Style Designator:	S	teel seal and wool seal
	S	tyle Designator:
Flange block	F	lange block
Shelf Life:	S	helf Life:
N/a	Ν	/a

NSN 3130-00-967-2840

Ball Bearing Unit - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A093a0

