NSN 3130-01-227-0663

Ball Bearing Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3130-01-227-0663

Nounting Slot Width:0.440 inchesMounting Slot Length:0.780 inchesBore Diameter:0.7500 inchesBase Thickness:0.470 inchesCenter To Center Distance Between Mounting Holes Along Width:3.780 inchesHousing Height:2.500 inchesHousing Width:5.000 inchesHousing Width:5.000 inchesHousing Width:5.000 inchesHousing Nidth:5.000 inchesHousing Nidth:5.000 inchesHousing Nidth:5.000 inchesHoldradie Regene8.000 inchesHousing Nidth:5.000 inchesHousing Nidth:5.000 inchesHousing Nidth:5.000 inchesHousing Nidth:5.000 inchesBuding Bement Groove Quantity:2Alignment Type:StandardAssemblylength:1.340 inchesStandardStandardStandardStandardStandardStandardStandardStandardBock Type:FixedStandardStandardLoctation:FixedStandardLoctation:Hole Assemblylength:Loctation:Hole Assemblylength:Loctation:Loctation:Loctation:Loctation:Loctation:Loctation:Loctation:Loctat	
Nounting Slot Length:0.780 inchesBore Diameter:0.7500 inchesBase Thickness:0.470 inchesCenter To Center Distance Between Mounting Holes Along Width:3.780 inchesHousing Height:2.500 inchesHousing Width:5.000 inchesLubrication Fitting Type:HydraulicBase Length:1.340 inchesRolling Element Groove Quantity:2Self-aligningInternal Fit-up Designation:StandardAssemblylength:1.340 inchesBase Length:1.340 inchesRolling Element Groove Quantity:2Alignent Type:Self-aligningInternal Fit-up Designation:StandardAssemblylength:1.340 inchesBelock Type:ContactBick Type:FixedBittend Type:FixedBittend Type:ContactBittend Type:FixedSub endsLocation:Bittend Type:RadialHeight Form Bottom Of Base To Bore Centerline:1.250 inchesKubrication Fitting Angle From Horizontal Centerline:45.0 degreesKotaing Element Locking Method:	Mounting Slot Width:
0.780 inchesBore Diameter:0.7500 inchesBase Thickness:0.470 inchesCenter To Center Distance Between Mounting Holes Along Width:3.780 inchesHousing Height:2.500 inchesHousing Width:5.000 inchesHousing Width:5.000 inchesLubrication Fitting Type:HydraulicBase Length:1.340 inchesRolling Element Groove Quantity:2Alignment Type:Self-aligningInternal Fit-up Designation:StandardAssemblylength:1.340 inchesSelf Type:ContactBiock Type:FixedShaft End Type:ContactBoth endsLoad Capability Type:RadialHeight From Bottom Of Base To Bore Centerline:1.250 inchesLubrication Fitting Angle From Horizontal Centerline:45.0 degreesRotating Element Locking Method:	0.440 inches
Bore Diameter:0.7500 inchesBase Thickness:0.470 inchesCenter To Center Distance Between Mounting Holes Along Width:3.780 inchesHousing Height:2.500 inchesHousing Width:5.000 inchesHubrication Fitting Type:HydraulicBase Length:1.340 inchesRolling Element Groove Quantity:2Alignment Type:Self-aligningInternal Fit-up Designation:1.340 inchesSearbylength:1.340 inchesSelf-aligningInternal Fit-up Designation:1.340 inchesSear Type:ContactBick Type:FixedShaft End Type:ContactBick Type:FixedShaft End Type:ContactBick Type:FixedShaft End Type:ContactBick Type:FixedShaft End Type:ContactLaccation:Both endsLaclocation:Coloria:Shaft End Type:FixedShaft End Type:FixedShaft End Type:FixedShaft End Type:Coloria:Coloria:Coloria:Shaft End Type:Coloria:Shaft End Type:FixedShaft End Type:FixedShaft End Type:Coloria:Coloria:Coloria:Co	Mounting Slot Length:
0.7500 inches Base Thickness: 0.470 inches Center To Center Distance Between Mounting Holes Along Width: 3.780 inches Housing Height: 2.500 inches Housing Width: 5.000 inches Hubrication Fitting Type: Hydraulic Base Length: 1.340 inches Rolling Element Groove Quantity: 2 Alignment Type: Self-aligning Internal Fil-tup Designation: Standard Assemblylength: 1.340 inches Self Aligning Internal Fil-tup Designation: Standard Assemblylength: 1.340 inches Self Aligning Internal Fil-tup Designation: Standard Assemblylength: 1.340 inches Self Aligning Internal Fil-tup Designation: Standard Assemblylength: 1.340 inches Self Aligning Gontact Block Type: Fixed <td< th=""><th>0.780 inches</th></td<>	0.780 inches
Base Thickness: 0.470 inches Center To Center Distance Between Mounting Holes Along Width: 3.780 inches Housing Height: 2.500 inches Housing Width: 5.000 inches Lubrication Fitting Type: Hydraulic Base Length: 1.340 inches Rolling Element Groove Quantity: 2 Alignment Type: Self-aligning Internal Fit-up Designation: Standard Assemblylength: 1.340 inches Self-aligning Internal Fit-up Designation: 1.340 inches Seal Type: 1.340 inches Seal Type: 1.340 inches Seal Type: Contact Block Type: Fixed Staft End Type: Copen Seal Location: Eadeloutity Type: Radial Height From Bottom Of Base To Bore Centerline: 1.250 inches Lubrication Fitting Angle From Horizontal Centerline: 4.5.0 degrees <th>Bore Diameter:</th>	Bore Diameter:
0.470 inchesCenter To Center Distance Between Mounting Holes Along Width:3.780 inchesHousing Height:2.500 inchesHousing Width:5.000 inchesLubrication Fitting Type:HydraulicBase Length:1.340 inchesRolling Element Groove Quantity:2Bif-aligningInternal Fit-up Designation:StandardAssemblylength:1.340 inchesBoard Dype:ContactBiote Type:ContactBiote Type:ContactBiote Type:ContactBiote Type:ContactBiote Type:ContactBiote Type:ContactBiote Type:CopenStaft End Type:CopinStaft Section:Lada Capability Type:RadialHeight From Bottom Of Base To Bore Centerline:1.250 inchesLubrication Fitting Angle From Horizontal Centerline:45.0 degreesKotating Element Locking Method:	0.7500 inches
Center O Center Distance Between Mounting Holes Along Width: 3.780 inches Housing Height: 2.500 inches Housing Width: 5.000 inches Lubrication Fitting Type: Hydraulic Base Length: 1.340 inches Rolling Element Groove Quantity: 2 Alignment Type: Self-aligning Internal Fit-up Designation: Standard Assemblylength: 1.340 inches Seal Type: Contact Biock Type: Contact Contact Biock Type: Contact Biock Type: Contact Contact Biock Type: Contact Contact Biock Type: Contact Contact Contact Biock Type: Contact Co	Base Thickness:
3.780 inches Housing Height: 2.500 inches Housing Width: 5.000 inches Lubrication Fitting Type: Hydraulic Base Length: 1.340 inches Rolling Element Groove Quantity: 2 Alignment Type: Self-aligning Internal Fit-up Designation: Standard Assemblylength: 1.340 inches Seal Type: Contact Block Type: Cintact Block Type: Open Seal Location: Both ends Load Capability Type: Radial Height From Bottom Of Base To Bore Centerline: 1.250 inches Lubrication Fitting Angle From Horizontal Centerline: 4.5.0 degrees Rotating Element Locking Method:	0.470 inches
Housing Height:2.500 inchesHousing Width:5.000 inchesLubrication Fitting Type:HydraulicBase Length:1.340 inchesRolling Element Groove Quantity:2Alignment Type:Self-aligningInternal Fit-up Designation:StandardAssemblylength:1.340 inchesSeal Type:ContactBlock Type:FixedShaft End Type:OpenGeal Location:AcadagLocatoagHourd Capability Type:RadialHeight From Bottom Of Base To Bore Centerline:1.250 inchesKating Element Locking Method:	Center To Center Distance Between Mounting Holes Along Width:
2.500 inches Housing Width: 5.000 inches Lubrication Fitting Type: Hydraulic Base Length: 1.340 inches Rolling Element Groove Quantity: 2 Alignment Type: Self-aligning Internal Fit-up Designation: Standard Assemblylength: 1.340 inches Self Type: Contact Block Type: Fixed Shaft End Type: Open Self Location: Both ends Lorad Capability Type: Radial Height From Bottom Of Base To Bore Centerline: 1.250 inches Lubrication Fitting Angle From Horizontal Centerline: 45.0 degrees Kotating Element Locking Method:	3.780 inches
Housing Width:5.000 inchesLubrication Fitting Type:HydraulicBase Length:1.340 inchesRolling Element Groove Quantity:2Alignment Type:Self-aligningInternal Fit-up Designation:StandardAssemblylength:1.340 inchesSeal Type:ContactBlock Type:ContactBlock Type:FixedShaft End Type:OpenSeal Location:Both endsLocation:I.340 inchesFixedStandardHord Seal ContactBoth endsLocation:Solt IndiaLocation:Solt IndiaLocation:Solt IndiaLocation:I.350 inchesLubrication Fitting Angle From Horizontal Centerline:45.0 degreesKotating Element Locking Method:	Housing Height:
S.000 inchesLubrication Fitting Type:HydraulicBase Length:1.340 inchesRolling Element Groove Quantity:2Alignment Type:Self-aligningInternal Fit-up Designation:StandardAssemblylength:1.340 inchesSeal Type:ContactBlock Type:FixedShaft End Type:OpenSeal Location:Both endsLocation:Both endsLocation:RadialHeight From Bottom Of Base To Bore Centerline:1.250 inchesSto. degreesRotating Element Locking Method:	2.500 inches
Lubrication Fitting Type:HydraulicBase Length:1.340 inchesRolling Element Groove Quantity:2Alignment Type:Self-aligningInternal Fit-up Designation:StandardAssemblylength:1.340 inchesSeal Type:ContactBlock Type:FixedStaft End Type:OpenSeal Location:Both endsLoad Capability Type:RadialHeight From Bottom Of Base To Bore Centerline:1.250 inchesSubrication Fitting Angle From Horizontal Centerline:45.0 degreesRotating Element Locking Method:	Housing Width:
HydraulicBase Length:1.340 inchesRolling Element Groove Quantity:2Alignment Type:Self-aligningInternal Fit-up Designation:StandardAssemblylength:1.340 inchesSeal Type:ContactBlock Type:FixedStaft End Type:OpenSeal Location:Edu endsLozation:I.320 inchesFixedStaft End Type:OpenSeal Location:I.250 inchesHeight From Bottom Of Base To Bore Centerline:1.250 inchesKubrication Fitting Angle From Horizontal Centerline:45.0 degreesRotating Element Locking Method:	5.000 inches
Base Length: 1.340 inches Rolling Element Groove Quantity: 2 Alignment Type: Self-aligning Internal Fit-up Designation: Standard Assemblylength: 1.340 inches Seal Type: Contact Block Type: Fixed Shaft End Type: Open Seal Location: Both ends Lad Capability Type: Radial Height From Bottom Of Base To Bore Centerline: 1.250 inches Subjerees Action Fitting Angle From Horizontal Centerline: 45.0 degrees Rotating Element Locking Method:	Lubrication Fitting Type:
1.340 inchesRolling Element Groove Quantity:2Alignment Type:Self-aligningInternal Fit-up Designation:StandardAssemblylength:1.340 inchesSeal Type:ContactBlock Type:FixedShaft End Type:OpenSeal Location:Both endsLad Capability Type:RadialHeight From Bottom Of Base To Bore Centerline:1.250 inchesSubrication Fitting Angle From Horizontal Centerline:45.0 degreesRotating Element Locking Method:	Hydraulic
Rolling Element Groove Quantity:2Alignment Type:Self-aligningInternal Fit-up Designation:StandardAssemblylength:1.340 inchesSeal Type:ContactBlock Type:FixedShaft End Type:OpenSeal Location:RadialHeight From Bottom Of Base To Bore Centerline:1.250 inchesSubrication Fitting Angle From Horizontal Centerline:45.0 degreesKotting Element Locking Method:	Base Length:
2 Alignment Type: Self-aligning Internal Fit-up Designation: Standard Assemblylength: 1.340 inches Seal Type: 1.340 inches Seal Type: Contact Block Type: Contact Block Type: Fixed Shaft End Type: Fixed Shaft End Type: Open Seal Location: Both ends Loga Capability Type: Radial Height From Bottom Of Base To Bore Centerline: 1.250 inches Lubrication Fitting Angle From Horizontal Centerline: 45.0 degrees	1.340 inches
Alignment Type:Self-aligningInternal Fit-up Designation:StandardAssemblylength:1.340 inchesSeal Type:ContactBlock Type:FixedShaft End Type:OpenSeal Location:Both endsLoad Capability Type:RadialHeight From Bottom Of Base To Bore Centerline:1.250 inchesSubrication Fitting Angle From Horizontal Centerline:45.0 degreesRotating Element Locking Method:	Rolling Element Groove Quantity:
Self-aligning Internal Fit-up Designation: Standard Assemblylength: 1.340 inches Seal Type: Contact Block Type: Contact Block Type: Fixed Shaft End Type: Open Seal Location: Both ends Load Capability Type: Radial Height From Bottom Of Base To Bore Centerline: 1.250 inches Lubrication Fitting Angle From Horizontal Centerline: 45.0 degrees	2
Internal Fit-up Designation: Standard Assemblylength: 1.340 inches Seal Type: Contact Biock Type: Contact Biock Type: Fixed Shaft End Type: Open Seal Location: Both ends Load Capability Type: Radial Height From Bottom Of Base To Bore Centerline: 1.250 inches Lubrication Fitting Angle From Horizontal Centerline: 45.0 degrees	Alignment Type:
Standard Assemblylength: 1.340 inches Seal Type: Contact Block Type: Fixed Shaft End Type: Open Seal Location: Both ends Load Capability Type: Radial Height From Bottom Of Base To Bore Centerline: 1.250 inches Lubrication Fitting Angle From Horizontal Centerline: 45.0 degrees	Self-aligning
Assemblylength:1.340 inchesSeal Type:ContactBlock Type:FixedShaft End Type:OpenSeal Location:Both endsLoad Capability Type:RadialHeight From Bottom Of Base To Bore Centerline:1.250 inchesLubrication Fitting Angle From Horizontal Centerline:45.0 degreesRotating Element Locking Method:	
1.340 inches Seal Type: Contact Block Type: Fixed Shaft End Type: Open Seal Location: Both ends Load Capability Type: Radial Height From Bottom Of Base To Bore Centerline: 1.250 inches Lubrication Fitting Angle From Horizontal Centerline: 45.0 degrees	Standard
Seal Type:ContactBlock Type:FixedShaft End Type:OpenSeal Location:Both endsLoad Capability Type:RadialHeight From Bottom Of Base To Bore Centerline:1.250 inchesLubrication Fitting Angle From Horizontal Centerline:45.0 degreesRotating Element Locking Method:	
Contact Block Type: Fixed Fixed Shaft End Type: Open Seal Location: Both ends Load Capability Type: Radial Height From Bottom Of Base To Bore Centerline: 1.250 inches Lubrication Fitting Angle From Horizontal Centerline: 45.0 degrees Rotating Element Locking Method:	
Block Type:FixedShaft End Type:OpenSeal Location:Both endsLoad Capability Type:RadialHeight From Bottom Of Base To Bore Centerline:1.250 inchesLubrication Fitting Angle From Horizontal Centerline:45.0 degreesRotating Element Locking Method:	Seal Type:
Fixed Shaft End Type: Open Seal Location: Both ends Load Capability Type: Radial Height From Bottom Of Base To Bore Centerline: 1.250 inches Lubrication Fitting Angle From Horizontal Centerline: 45.0 degrees Rotating Element Locking Method:	
Shaft End Type: Open Seal Location: Both ends Load Capability Type: Radial Height From Bottom Of Base To Bore Centerline: 1.250 inches Lubrication Fitting Angle From Horizontal Centerline: 45.0 degrees Rotating Element Locking Method:	
OpenSeal Location:Both endsLoad Capability Type:RadialHeight From Bottom Of Base To Bore Centerline:1.250 inchesLubrication Fitting Angle From Horizontal Centerline:45.0 degreesRotating Element Locking Method:	
Seal Location: Both ends Load Capability Type: Radial Height From Bottom Of Base To Bore Centerline: 1.250 inches Lubrication Fitting Angle From Horizontal Centerline: 45.0 degrees Rotating Element Locking Method:	
Both endsLoad Capability Type:RadialHeight From Bottom Of Base To Bore Centerline:1.250 inchesLubrication Fitting Angle From Horizontal Centerline:45.0 degreesRotating Element Locking Method:	
Load Capability Type: Radial Height From Bottom Of Base To Bore Centerline: 1.250 inches Lubrication Fitting Angle From Horizontal Centerline: 45.0 degrees Rotating Element Locking Method:	
Radial Height From Bottom Of Base To Bore Centerline: 1.250 inches Lubrication Fitting Angle From Horizontal Centerline: 45.0 degrees Rotating Element Locking Method:	
Height From Bottom Of Base To Bore Centerline: 1.250 inches Lubrication Fitting Angle From Horizontal Centerline: 45.0 degrees Rotating Element Locking Method:	
1.250 inches Lubrication Fitting Angle From Horizontal Centerline: 45.0 degrees Rotating Element Locking Method:	
Lubrication Fitting Angle From Horizontal Centerline: 45.0 degrees Rotating Element Locking Method:	
45.0 degrees Rotating Element Locking Method:	
Rotating Element Locking Method:	
	-
Straight sleeve	
	Straight sleeve

NSN 3130-01-227-0663

Ball Bearing Unit - Page 2 of 2



Mounting Hole Type:

Slotted

Special Features:

No locking collar provided; lube fitting compatable grease gun 10915142

Lubrication Material:

Grease

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel bearing

Style Designator:

Pillow block, solid

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A093a0

Mil-std (military Standard):

Mil-g-23827 spec.