

View Online at <https://aerobasegroup.com/nsn/3130-01-232-0538>

Counterbore Diameter:

2.000 inches

Counterbore Depth:

1.875 inches

Mounting Hole Diameter:

Between 1.282 inches and 1.284 inches

Bore Diameter:

Between 2.0000 inches and 2.0010 inches

Base Thickness:

2.000 inches

Center To Center Distance Between Mounting Holes Along Width:

15.000 inches

Housing Height:

8.250 inches

Housing Width:

17.750 inches

Lubrication Fitting Type:

Pipe plug

Base Length:

2.750 inches

Assemblylength:

4.4900 inches

Shaft End Type:

Open

Height From Bottom Of Base To Bore Centerline:

6.500 inches

Lubrication Fitting Angle From Horizontal Centerline:

90.0 degrees

Mounting Hole Type:

Round, unthreaded, counterbored

Special Features:

Second bearing mounting hole 1.000 in. Diameter min to 1.001 in. Diameter max, centered 3.500 in. Right of vert cl, 0.750 in. Below horiz cl;
third bearing mounting hole 0.750 in. Diameter min to 0.751 in. Diameter maximum centered 5.500 in. Left of vert cl, 1.250 in. Below horiz cl;
0.250 in. Diameter through hole from base to first bore, tap 0.125 ptf; two 0.250-20unc-2b tapped through holes in face centered 1.120 in.
Right of third bearing mounting hole, 0.380 above and below third bearing mounting hole horiz cl

Material:

Copper alloy 958

Material Specification:

Mil-b-24480 military specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A093a0

Mil-std (military Standard):

Mil-b-24480 spec.