
NSN 3130-01-232-0538

Bearing Unit Housing - Page 1 of 2





Counterbore Diameter: 2.000 inches **Counterbore Depth:** 1.875 inches **Mounting Hole Diameter:** Between 1.282 inches and 1.284 inches **Bore Diameter:** Between 2.0000 inches and 2.0010 inches **Base Thickness:** 2.000 inches Center To Center Distance Between Mounting Holes Along Width: 15.000 inches **Housing Height:** 8.250 inches Housing Width: 17.750 inches Lubrication Fitting Type: Pipe plug **Base Length:** 2.750 inches Assemblylength: 4.4900 inches Shaft End Type: Open Height From Bottom Of Base To Bore Centerline: 6.500 inches Lubrication Fitting Angle From Horizontal Centerline: 90.0 degrees Mounting Hole Type:

Round, unthreaded, counterbored

Special Features:

Second bearing mounting hole 1.000 in. Diameter min to 1.001 in. Diameter max, centered 3.500 in. Right of vert cl, 0.750 in. Below horiz cl; third bearing mounting hole 0.750 in. Diameter min to 0.751 in. Diameter maximum centered 5.500 in. Left of vert cl, 1.250 in. Below horiz cl; 0.250 in. Diameter through hole from base to first bore, tap 0.125 ptf; two 0.250-20unc-2b tapped through holes in face centered 1.120 in. Right of third bearing mounting hole, 0.380 above and below third bearing mounting hole horiz cl

Material:

Copper alloy 958

Material Specification:

Mil-b-24480 military specification single material response

Shelf Life:

N/a

Unit Of Measure:

- ---
- Demilitarization:

NSN 3130-01-232-0538

Bearing Unit Housing - Page 2 of 2

Fiig:

A093a0

Mil-std (military Standard):

Mil-b-24480 spec.

