
Plain Bearing Unit - Page 1 of 2



Counterbore Diameter:

0.594 inches

Counterbore Depth:

0.500 inches

Mounting Hole Diameter:

0.406 inches

Bore Diameter:

0.9060 inches

Base Thickness:

0.750 inches

Center To Center Distance Between Mounting Holes Along Width:

0.875 inches

Housing Height:

3.250 inches

Housing Length:

1.000 inches

Housing Width:

2.750 inches

Base Length:

0.875 inches

Alignment Type:

Rigid

Assemblylength:

1.000 inches

Shaft End Type:

Closed

Load Capability Type:

Radial

Height From Bottom Of Base To Bore Centerline:

2.375 inches

Mounting Hole Type:

Round, unthreaded, counterbored

Special Features:

Mounting holes drilled horiz through base face; two 0.313 in. Diameter through base 0.625 in. C to c from mounting holes

Material:

Copper alloy

Material Specification:

Mil-b-21230 military specification single material response

Style Designator:

Pillow block, solid

Shelf Life:

N/a



NSN 3130-01-240-5376

Plain Bearing Unit - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A093a0

Mil-std (military Standard):

Mil-b-21230 spec.

