

View Online at <https://aerobasegroup.com/nsn/3130-01-271-6024>

Pilot Diameter:

Between 4.4985 inches and 4.4995 inches

Bolt Circle Diameter:

5.281 inches

Flange Thickness:

Between 0.307 inches and 0.317 inches

Mounting Hole Diameter:

Between 0.211 inches and 0.223 inches

Bore Diameter:

Between 1.2400 inches and 1.2600 inches

Housing Diameter:

Between 5.714 inches and 5.724 inches

Housing Length:

0.781 inches

Assemblylength:

0.937 inches

Pilot Length:

Between 0.464 inches and 0.474 inches

Shaft End Type:

Open

Mounting Hole Type:

Round, unthreaded

Special Features:

3 holes csk 90 degrees apart to 0.215 in. Dia, 0.190-32 unf-2b equally spaced; 3 holes through one wall 0.500 in. Dia; 1 pin grooved headless per ms35678-23

Material:

Steel comp 630 inner liner

Material Specification:

Qq-a-225/8 federal specification single material response inner liner

Surface Treatment:

Anodize inner liner

Surface Treatment Specification:

Mil-a-8625, type 2, class 1 military specification single treatment response housing

Style Designator:

Flange cartridge block

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A093a0

Mil-std (military Standard):

Mil-a-8625 spec.