## NSN 3130-01-274-6193

Bearing Unit Housing - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/3130-01-274-6193   |
|---|
| Pilot Diameter:   |
| Between 2.4994 inches and 2.5000 inches   |
| Counterbore Diameter:   |
| Between 0.327 inches and 0.337 inches   |
| Counterbore Depth:  |
| 0.203 inches  |
| Bolt Circle Diameter:   |
| 3.203 inches  |
| Flange Thickness:   |
| Between 0.339 inches and 0.349 inches   |
| Mounting Hole Diameter:   |
| Between 0.211 inches and 0.223 inches   |
| Bore Diameter:  |
| Between 1.0180 inches and 1.0220 inches   |
| Housing Diameter:   |
| Between 3.740 inches and 3.760 inches   |
| Housing Length:   |
| 1.746 inches  |
| Assemblylength:   |
| 1.746 inches  |
| Pilot Length:   |
| Between 0.353 inches and 0.357 inches   |
| Shaft End Type:   |
| Open  |
| Mounting Hole Type:   |
| Round, unthreaded, counterbored   |
| Special Features:   |
| 3 holes tap drill through csk 90 degrees to 0.215 in. Dia, 190-32 unf-2b equally spaced; item consist of one pin, straight headless, 2 plug |
| assembly sealing  |
| Material:   |
| Aluminum alloy 6061   |
| Material Specification:   |
| Qq-a-225/8 federal specification single material response   |
| Surface Treatment:  |
| Anodize   |
| Surface Treatment Specification:  |
| Mil-a-8625, type 2, class 1 military specification single treatment response  |
| Style Designator:   |
| Flange cartridge block  |
| Shelf Life:   |

--

N/a

**Unit Of Measure:** 

## NSN 3130-01-274-6193

Bearing Unit Housing - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A093a0

Mil-std (military Standard):

Mil-a-8625 spec.