

View Online at <https://aerobasegroup.com/nsn/3130-01-274-6193>

Pilot Diameter:

Between 2.4994 inches and 2.5000 inches

Counterbore Diameter:

Between 0.327 inches and 0.337 inches

Counterbore Depth:

0.203 inches

Bolt Circle Diameter:

3.203 inches

Flange Thickness:

Between 0.339 inches and 0.349 inches

Mounting Hole Diameter:

Between 0.211 inches and 0.223 inches

Bore Diameter:

Between 1.0180 inches and 1.0220 inches

Housing Diameter:

Between 3.740 inches and 3.760 inches

Housing Length:

1.746 inches

Assemblylength:

1.746 inches

Pilot Length:

Between 0.353 inches and 0.357 inches

Shaft End Type:

Open

Mounting Hole Type:

Round, unthreaded, counterbored

Special Features:

3 holes tap drill through csk 90 degrees to 0.215 in. Dia, 190-32 unf-2b equally spaced; item consist of one pin, straight headless, 2 plug assembly sealing

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-225/8 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, class 1 military specification single treatment response

Style Designator:

Flange cartridge block

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A093a0

Mil-std (military Standard):

Mil-a-8625 spec.