

View Online at <https://aerobasegroup.com/nsn/3130-01-274-6193>

**Pilot Diameter:**

Between 2.4994 inches and 2.5000 inches

**Counterbore Diameter:**

Between 0.327 inches and 0.337 inches

**Counterbore Depth:**

0.203 inches

**Bolt Circle Diameter:**

3.203 inches

**Flange Thickness:**

Between 0.339 inches and 0.349 inches

**Mounting Hole Diameter:**

Between 0.211 inches and 0.223 inches

**Bore Diameter:**

Between 1.0180 inches and 1.0220 inches

**Housing Diameter:**

Between 3.740 inches and 3.760 inches

**Housing Length:**

1.746 inches

**Assemblylength:**

1.746 inches

**Pilot Length:**

Between 0.353 inches and 0.357 inches

**Shaft End Type:**

Open

**Mounting Hole Type:**

Round, unthreaded, counterbored

**Special Features:**

3 holes tap drill through csk 90 degrees to 0.215 in. Dia, 190-32 unf-2b equally spaced; item consist of one pin, straight headless, 2 plug assembly sealing

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-225/8 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2, class 1 military specification single treatment response

**Style Designator:**

Flange cartridge block

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A093a0

**Mil-std (military Standard):**

Mil-a-8625 spec.