

View Online at <https://aerobasegroup.com/nsn/3130-01-293-5471>

Pilot Diameter:

2.3750 inches

Tempurature Rating:

-28.0 degrees celsius and 65.0 degrees celsius

Bolt Circle Diameter:

4.3750 inches

Flange Thickness:

Between 0.4700 inches and 0.7500 inches

Mounting Hole Diameter:

0.4060 inches

Bore Diameter:

Between 1.4380 inches and 1.4385 inches

Housing Diameter:

5.2500 inches

Rolling Element Groove Quantity:

2

Alignment Type:

Rigid

Internal Fit-up Designation:

Standard

Assemblylength:

2.8900 inches

Pilot Length:

1.5300 inches

Seal Type:

Labyrinth

Block Type:

Fixed

Shaft End Type:

Open

Seal Location:

Both ends

Collar Location:

One end

Load Capability Type:

Radial

Features Provided:

Drain plug

Rotating Element Locking Method:

Setscrew locking collar

Mounting Hole Type:

Round, unthreaded

Material:

Steel housing

Material Specification:

Mil-r-7362, type 1 military specification single material response seal

Style Designator:

Flange cartridge block

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A093a0

Mil-std (military Standard):

Mil-r-7362 spec.