NSN 3130-01-309-7180

Bearing Unit Housing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3130-01-309-7180

| Bolt Circle Diameter: 4.7500 inches Flange Thickness: 0.7500 inches | |
|--|------------------|
| Flange Thickness: | |
| | |
| 0.7500 inches | |
| | |
| Mounting Hole Diameter: | |
| Between 0.4360 inches and 0.4450 inches | |
| Bore Diameter: | |
| 1.6880 inches | |
| Overall Outside Diameter: | |
| 5.6200 inches | |
| Mounting Hole Type: | |
| Round, unthreaded | |
| Special Features: | |
| Eight additional holes 0.250-28 unf-2bx0.625 in. Min dp on 2.500 in. Bolt circle; id cbore 2.00 in. Min to 2.003 in. Max; or | ne end of flange |
| internally threaded 0.250-28 unf-2bx 0.25 in. Min dp 0.187 in. Thru | |
| Material: | |
| Steel comp e4340 | |
| Material Specification: | |
| Mil-s-5000, cond c1 military specification single material response | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A093a0 | |
| Mil-std (military Standard): | |
| Mil-s-5000 spec. | |