NSN 3130-01-348-3792

Ball Bearing Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3130-01-348-3792

| Mounting Hole Dismotor. | | | | |
|--|--|--|--|--|
| Mounting Hole Diameter: | | | | |
| 0.1562 inches | | | | |
| Bore Diameter: | | | | |
| 0.3745 inches | | | | |
| Base Thickness: | | | | |
| 0.1875 inches | | | | |
| Center To Center Distance Between Mounting Holes Along Width: | | | | |
| Between 1.4270 inches and 1.4470 inches | | | | |
| Center To Center Distance Between Mounting Holes Along Length: | | | | |
| Between 2.2400 inches and 2.2600 inches | | | | |
| Housing Height: | | | | |
| 0.9375 inches | | | | |
| Housing Length: | | | | |
| 2.7500 inches | | | | |
| Housing Width: | | | | |
| 1.7500 inches | | | | |
| Lubrication Fitting Type: | | | | |
| Wick | | | | |
| Rolling Element Groove Quantity: | | | | |
| 2 | | | | |
| Alignment Type: | | | | |
| Rigid | | | | |
| Internal Fit-up Designation: | | | | |
| Standard | | | | |
| Seal Type: | | | | |
| Contact | | | | |
| Block Type: | | | | |
| Fixed | | | | |
| Shaft End Type: | | | | |
| Open | | | | |
| Seal Location: | | | | |
| Both ends | | | | |
| Load Capability Type: | | | | |
| Radial and thrust | | | | |
| Height From Bottom Of Base To Bore Centerline: | | | | |
| Between 0.4970 inches and 0.5030 inches | | | | |
| Rotating Element Locking Method: | | | | |
| Straight sleeve | | | | |
| Mounting Hole Type: | | | | |
| Round, unthreaded | | | | |
| Special Features: | | | | |

Two ball bushings included

NSN 3130-01-348-3792

Ball Bearing Unit - Page 2 of 2



| | er | |
|--|----|--|
| | | |
| | | |

Aluminum alloy 6061 housingstainless steel seal

Style Designator:

Pillow block, twin, adjustable diameter

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A093a0