

View Online at <https://aerobasegroup.com/nsn/3220-01-270-7416>

Mounting Type:

Floor

Current Type:

Ac

Center To Center Distance:

39.000 inches

Furnished Items And Quantity:

1 of ea safety shield, drive center, cup center, tool support base, 12 in. Tool support, 6 in. Tool support, 3 in. Face plate, motor pulley (5/8 in. Bore), upper v-belt, lower v-belt

Feed Type:

Hand

Electric Motor Horsepower Rating:

0.750

Power Source:

Electric motor

Bed Type:

Fixed gap

Spindle Speed Range In Rpm:

+340.0/+3600.0

Headstock Drive Type:

Variable speed motor for belted motor

Err Default:

Err default

Err Default:

Err default

Err Default:

Err default

Headstock Hollow Spindle Drive Center Feature:

Included

Headstock Faceplate/chuck Attachment Method:

Any acceptable

Tool Support Type:

Tool post carriage

Voltage In Volts:

115.0

Phase:

Single

Special Features:

Variable speed spindle

Frequency In Hertz:

60.0

Specification Or Standard:

li type and 12 size and 1 style

Departure From Cited Document:

As modified by voltage in volts and phase

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T221-e