## NSN 3220-01-392-8369

Woodworking Surfacer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3220-01-392-8369 **Mounting Type:** Floor **Current Type:** Ac **Material Accommodated Thickness:** Between 0.125 inches and 8.000 inches Frequency In Hertz: 60.0 **Furnished Items And Quantity:** High speed, heat treated tool steel knives, 4; knife round cutterhead mounted in sealed ball bearings, 4; cutterhead guard, 1; knife setting gauge, 1; jack screws, 4; cutterhead pulley, 1; bed rollers, 4 **Operating Voltage In Volts:** Between 230.0 and 460.0 **Horsepower Rating:** 15.00 **Power Source:** Electric motor **Bed Type:** Screw **Power Feed Roll Quantity:** 4 **Material Width Accommodated:** 24.000 inches **Cutter Head Quantity:** 1 **Cutter Head Cylinder Diameter:** 4.125 inches **Cutter Head Cutting Circle Diameter:** 4.375 inches **Cutter Head Knife Quantity: Cutter Head Knifelength:** 24.250 inches Phase: Three **Special Features:** Sectional infeed rolls and chipbreaker, motor mount base, 1 1/2 hp feed drive motor, motor pulley, belts and belt guard; 4 in. Diameter feed rollers; 4 in. Diameter bed rollers; variable speed feed range 20 fpm to 100 fpm; weight with motor, domestic crated 2885 pounds; 24 in. By 48 in. Bed; recommended cutterhead speed, belted drive 4800 rpm Shelf Life: N/a **Unit Of Measure:** 

N

**Demilitarization:** 

## NSN 3220-01-392-8369

Woodworking Surfacer - Page 2 of 2



Fiig:

T220-d