## NSN 3220-01-392-8369

Woodworking Surfacer - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/3220-01-392-8369



## Mounting Type:

Floor

**Current Type:** 

Ac

## Material Accommodated Thickness:

Between 0.125 inches and 8.000 inches

## **Frequency In Hertz:**

60.0

#### **Furnished Items And Quantity:**

High speed, heat treated tool steel knives, 4; knife round cutterhead mounted in sealed ball bearings, 4; cutterhead guard, 1; knife setting gauge, 1; jack screws, 4; cutterhead pulley, 1; bed rollers, 4

## **Operating Voltage In Volts:**

Between 230.0 and 460.0

### **Horsepower Rating:**

15.00

#### **Power Source:**

Electric motor

## Bed Type:

Screw

**Power Feed Roll Quantity:** 

```
4
```

**Material Width Accommodated:** 

24.000 inches

**Cutter Head Quantity:** 

1

**Cutter Head Cylinder Diameter:** 

4.125 inches

**Cutter Head Cutting Circle Diameter:** 

4.375 inches

**Cutter Head Knife Quantity:** 

4

#### **Cutter Head Knifelength:**

24.250 inches

#### Phase:

Three

#### **Special Features:**

Sectional infeed rolls and chipbreaker, motor mount base, 1 1/2 hp feed drive motor, motor pulley, belts and belt guard; 4 in. Diameter feed rollers; 4 in. Diameter bed rollers; variable speed feed range 20 fpm to 100 fpm; weight with motor, domestic crated 2885 pounds; 24 in. By 48 in. Bed; recommended cutterhead speed, belted drive 4800 rpm

## Shelf Life:

N/a

#### Unit Of Measure:

- **Demilitarization:**

# NSN 3220-01-392-8369

Woodworking Surfacer - Page 2 of 2

Fiig: T220-d

