

View Online at <https://aerobasegroup.com/nsn/3405-00-294-9591>

Mounting Type:

Floor

Current Type:

Ac

Frequency Rating:

60.000 hertz

Accessory Components And Quantity:

Aluminum oxide abrasive band, 1 in. W, 12 ea, no. 50, no. 80, no. 150; saw blade guide adapter set, 90 degrees 1; drive belt set 1; flexible back conventional tooth set, band saw blade, raker set, 100 ft coils per ggg-b-421, type 1, style 1, 8 coils 0.025 in. Thk, w in in. And teeth as follows 1/8 14, 1/8 18, 1/8 24, 1/4 10, 1/4 18, 1/4 24, 1/2 6, 1/2 10, 2 coils 0.032 in. Thk, 3/4 10; skip tooth flexible back band saw blade, 100 ft coils per ggg-b-421, type 1, style 2, 2 coils 0.025 in. Thk, w in in. And teeth as follows 1/4 6, 1/2 4, 1 coil 0.032 in. Thk, 3/4 3; 1 pump and chip blower, 1 circle cutting attachment; 1 cut off-mitre attachment; med cut flat bastard file bands 1 ea 1/4 in. W, 1/2 in. W; oval bastard file band med cut 1/4 in. W bands 1 set; file band guides 1 set ea for 1/4 in. 1/2 in. W bands; 1 set roller back-up bearing for 1/2, 3/16, 1/4, 3/8, 1/2, 3/4 in. W/blades; 1 holding jaw; 1 shielded table light; 1 etching pencil; 1 rip fence

Frame Type:

Rigid

Voltage Rating:

208.000 volts

Feed Method:

Work into cutting band

Rotational Speed Rating In Rpm:

Any acceptable

Horsepower Rating:

1.500

Throat Depth:

15.250 inches

Braking Facility:

Not included

Drive Method:

Electric motor

Table Length:

24.000 inches

Table Width:

24.000 inches

Electric Motor Quantity:

1

Table Type:

Tilting

Table Right Tilt Angle In Deg:

45.0

Table Left Tilt Angle In Deg:

10.0

Band Type For Which Designed:

File or saw blade

File Maximum Length Accommodated:

Blade Maximum Length Accommodated:

Any acceptable

Blade Maximum Width Accommodated:

0.750 inches

Vise:

Not provided

Distance Between Guide And Table:

12.000 inches

Cutting Speed Range:

+50.0 to 5200.0 feet per minute

Infinite Cutting Speed Feature:

Provided

Power Feed Feature:

Provided

Built-in Coolant System:

Not included

Integral Butt Welder:

Included

Integral Grinder:

Included

Phase:

Three

Special Features:

Accessory components and qty, file band guides 1/4 in. W, 1 set, file band guides 1/2 in. W, 1 set; back-up roller bearing for 1/8, 3/16, 1/4, 3/8, 1/2, and 3/4 in. W blades, 1 set; jaw holding 1; shielded table light 1; etching pencil 1; rip fence 1

Specification Or Standard:

16 size

Departure From Cited Designator:

As modified by voltage rating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T294-s