

View Online at <https://aerobasegroup.com/nsn/3405-00-409-0063>

Mounting Type:

Floor

Current Type:

Ac

Frequency Rating:

60.0 hertz

Accessory Components And Quantity:

Fence, rip, 18 in., 1; belt attachment, sanding abrasive, 1; welder and grinder, butt, 1; lamp attachment, 1; sliding, straight and angle cut-off, 1; lamp attachment, sliding jig, 1; spare drive belt set, 1; blade, skip tooth, 100 ft.Coil, aluminum and plastic cutting, 1; raker set, flexible back, conventional tooth, 1/2 in.Wide, 14 tooth, 100 ft.Coil, 1; blade, 1/2 in.Wide, 24 tooth, pipe and channel cutting, 100 ft.Coil, 1; belt, sanding, coarse grit, 3; belt, sanding, medium grit, 3

Frame Type:

Rigid

Voltage Rating:

115.0 volts

Rotational Speed Rating In Rpm:

1725.0

Horsepower Rating:

0.750

Throat Depth:

13.750 inches

Braking Facility:

Not included

Drive Method:

Electric motor

Table Length:

14.000 inches

Table Width:

14.000 inches

Electric Motor Quantity:

1

Table Type:

Tilting

Table Right Tilt Angle In Deg:

45.0

Table Left Tilt Angle In Deg:

10.0

Band Type For Which Designed:

Saw blade

Blade Maximum Length Accommodated:

94.000 inches

Blade Maximum Width Accommodated:

0.750 inches

Vise:

Not provided

Distance Between Guide And Table:

6.250 inches

Cutting Speed Range:

+40.0/+3000.0 feet per minute

Cutting Speed Quantity:

8

Power Feed Feature:

Not provided

Built-in Coolant System:

Not included

Integral Butt Welder:

Not included

Integral Grinder:

Not included

Phase:

Single

Reference Number Differentiating Characteristics:

As differentiated by the drive method, electric motor requirements and accessory components requirement

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T294-s