NSN 3405-00-542-1328

Metal Cutting Band Saw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3405-00-542-1328

| Mounting Type: |
|--|
| Floor |
| Current Type: |
| Ac |
| Frequency Rating: |
| 60.000 hertz |
| Accessory Components And Quantity: |
| Abrasive bands, no.50, 80, 150 aluminum oxide, 1 in.W 12; adapter, saw blade guide, 90 degrees angle, 1; belt drive, 1 set; blade, band |
| saw, flexible back, conventional tooth, raker, 1 set; 100 ft coils, in accordance w/ggg-b-421, type 1, style 1, 1/8 in. W, 0.025 in.Thk, 1; pitch, |
| 14, 18, 24; coil, 1/4 in.W, 0.025 in.Thk, 1; pitch, 10, 18, 24; coil, 1/2 in.W, 0.025 in.Thk, 1; pitch, 6, 10; coil, 3/4 in.W.0.032 in.Thk, 1; ptich, 6, |
| 10; coil, blade, band saw, flexible back, skip tooth, 100 ft coils in accordance w/ggg-b-421, type 1, style 2, 1/4in.W, 0.025 in.Thk, 1; pitch, 6; |
| coil, 1/2 in.W, 0.025 in thk, 1; pitch, 4; coil, 3/4 inw, 0.032 in. Thk, 1; pitch, 3; coil, circle cutting attachment, 1; cut-off-mitre attachment, file |
| band, flat bastard, medium cut, 1/4 in.W, 1; file band, flat bastard, medium cut, 1/2 in.W, 1; file band, oval bastard, medium cut, 1/4&1/2 in.W, |
| 1; file band, flat bastard, medium cut, 3/8 in.W, 1; file band, oval bastard, med.Cut, 3/8 in.W, 1; guides, abrasive band, for 1 in.W band, 1 set; |
| guides, file band, for 1/4, 3/8, 1/2 in.W band, 1 set |
| Frame Type: |
| Rigid |
| Voltage Rating: |
| 220.0 volts or 440.0 volts |
| Feed Method: |
| Work into cutting band |
| Rotational Speed Rating In Rpm: |
| Not rated |
| Horsepower Rating: |
| 3.000 |
| Throat Depth: |
| 26.000 inches |
| Braking Facility: |
| Not included |
| Drive Method: |
| Electric motor |
| Table Length: |
| 26.000 inches |
| Table Width: |
| 26.000 inches |
| Electric Motor Quantity: |
| |
| Table Type: |
| Tilting Table Bight Tilt Angle In Dogu |
| Table Right Tilt Angle In Deg: |
| 45.000 Table Left Tilt Angle In Dog. |
| Table Left Tilt Angle In Deg: |
| 5.000 |

Band Type For Which Designed:

NSN 3405-00-542-1328Metal Cutting Band Saw - Page 2 of 2



| Diada Mayinguna Width Assange adatad |
|--|
| Blade Maximum Width Accommodated: |
| 1.000 inches |
| Vise: |
| Not provided |
| Distance Between Guide And Table: |
| 12.000 inches |
| Cutting Speed Range: |
| +50.0 to 4000.0 feet per minute |
| Infinite Cutting Speed Feature: |
| Provided |
| Power Feed Feature: |
| Provided |
| Built-in Coolant System: |
| Not included |
| Integral Butt Welder: |
| Included |
| Integral Grinder: |
| Included |
| Phase: |
| Three |
| Special Features: |
| Guides, saw blade, w/ball bearing back-up roller for 1/8, 3/16, 1/4, 3/8, 1/2and 3/4 in.W blades, 1 set; jaw, workholding, light, table, shielded, |
| pencil, etching, rip fence, polishing band attachment, 1; special hand tools, 1 set; felt wheel lubricator or mist coolant, 1; band speed and |
| tension indicator dials, 1; metal cutting, carbon band saw blades 1/4, 1/2, 3/4 in., 1 ea; chart or selector dial which shall indicate the |
| recommended cutting, filing, friction sawing, grinding, polishing, and high speed sawing speedsin surface feet per minute for |
| variousmaterials, the chart or selector dial shall also provide the recommended typetooth pitch; carbon, 1 set; high speed steel saw blades, 1 |
| set, for various thickness of plastics, wood, and ferrous and non-ferrous metal |
| Specification Or Standard: |
| 26 size |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T294-s |
| |
| |