

View Online at <https://aerobasegroup.com/nsn/3410-01-394-0503>

Special Features:

Dielectric system: reservoir capaci type 42 gallons; stainless tank; filter ebbco simplex hurricane with 1 cubic foot de-i unit; dielectric fluid-deionized water; bi-polar transistor pulse power supply circuit system; 15 amps output current; 4 steps output voltage selections; 22 steps pulse on-time selections; 32 steps frequency selections; 200/220 volt; ac; 60 hertz; 3 phase; 7 kva; unit dimensions: 28 in. Wide by 57 in. Deep by 72 in. High; unit weight 13420 pounds

General Description:

Hitachi model h-cut 203-m wire electrical discharge machine complete with hitachi mark-100 cnc control; 14 in. Color crt; background editing; workpiece dimensions: 18 in. Wide; 14 in. Deep; 6.7 in. High; workpiece weight 440 pounds; travel x axis 12.8 in.; travel y axis 9.8 in.; travel u and v axis $\pm .74$ in.; taper angle ± 12 degrees in 3 in.; positioning accuracy $\pm .0001$ in.; table feed rate 23.6 in. Per minute; wire diameter 0.004 in. Through 0.012 in.; wire feed rate 3.5 in./sec.; wire tension range 200 to 1700 grams; machine dimensions 76 in. Wide by 69 in. Deep by 76 in. High; machine weight 3300 pounds

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No