## NSN 3413-00-004-2317

Upright Drilling Machine - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3413-00-004-2317 **Mounting Type:** Floor **Electric Motor Power Rating:** 1.000 horsepower **Current Type:** Ac **Head Type:** Fixed **Fungus Resistant Treatment:** Not included **Radio Interference Shielding:** Not provided **Rotation Reversibility Feature:** Not included Feed Type: Power **Spindle Quantity: Main Drive Type:** Electric motor **Spindle Socket Taper Size:** 4 morse **Spindle Travel Distance:** 12.500 inches **Drilling Capability:** 1.500 in. Drilling capacity in cast iron **Column Type:** Round **Distance From Spindle Center To Column:** 21.000 inches **Base Working Surface Type: Base Working Surface Shape:** Rectangular **Base Working Surface Mounting Location:** Maximum Distance From Chuck/spindle Nose To Base Working Surface: 40.000 inches **Upper Working Surface Type:** Slotted w/center hole

Round

**Upper Working Surface Shape:** 

## **NSN 3413-00-004-2317**Upright Drilling Machine - Page 2 of 2



| Upper Working Surface Diameter:                                    |  |
|--|--|
| 16.375 inches  |  |
| Upper Working Surface Adjustment Feature:                          |  |
| ncluded  |  |
| Tilt Adjustment Direction And Angle In Deg:                        |  |
| 40.0 right   |  |
| Spindle Type:  |  |
| Tapered socket   |  |
| Spindle Speed Quantity:  |  |
| 3  |  |
| Spindle Speed Range In Rpm:  |  |
| +34.0 to 560.0   |  |
| Upper Working Surface Mounting Location:                           |  |
| Column   |  |
| Maximum Distance From Chuck/spindle Nose To Upper Working Surface: |  |
| 26.500 inches  |  |
| Voltage In Volts:  |  |
| 220.0 or 440.0   |  |
| Phase:   |  |
| Three  |  |
| Frequency In Hertz:  |  |
| 60.0   |  |
| Shelf Life:  |  |
| N/a  |  |
| Unit Of Measure:   |  |
| -  |  |
| Demilitarization:  |  |
| No   |  |
| Filg:  |  |
| Г317-f   |  |
|  |  |