## NSN 3413-00-004-2317

Upright Drilling Machine - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3413-00-004-2317 **Mounting Type:** Floor **Electric Motor Power Rating:** 1.000 horsepower **Current Type:** Ac **Head Type:** Fixed **Fungus Resistant Treatment:** Not included **Radio Interference Shielding:** Not provided **Rotation Reversibility Feature:** Not included Feed Type: Power **Spindle Quantity: Main Drive Type:** Electric motor **Spindle Socket Taper Size:** 4 morse **Spindle Travel Distance:** 12.500 inches **Drilling Capability:** 1.500 in. Drilling capacity in cast iron **Column Type:** Round **Distance From Spindle Center To Column:** 21.000 inches **Base Working Surface Type: Base Working Surface Shape:** Rectangular **Base Working Surface Mounting Location:** Maximum Distance From Chuck/spindle Nose To Base Working Surface: 40.000 inches **Upper Working Surface Type:** Slotted w/center hole

Round

**Upper Working Surface Shape:** 

## **NSN 3413-00-004-2317**Upright Drilling Machine - Page 2 of 2



Upper Working Surface Diameter:	
16.375 inches	
Upper Working Surface Adjustment Feature:	
ncluded	
Tilt Adjustment Direction And Angle In Deg:	
40.0 right	
Spindle Type:	
Tapered socket	
Spindle Speed Quantity:	
3	
Spindle Speed Range In Rpm:	
+34.0 to 560.0	
Upper Working Surface Mounting Location:	
Column	
Maximum Distance From Chuck/spindle Nose To Upper Working Surface:	
26.500 inches	
Voltage In Volts:	
220.0 or 440.0	
Phase:	
Three	
Frequency In Hertz:	
60.0	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Filg:	
Г317-f	