NSN 3413-00-165-4136

Upright Drilling Machine - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/3413-00-165-4136 **Mounting Type:** Bench **Electric Motor Power Rating:** 0.500 horsepower **Current Type:** Ac **Head Type:** Sliding **Fungus Resistant Treatment:** Not included **Radio Interference Shielding:** Not provided **Rotation Reversibility Feature:** Not included Feed Type: Hand **Electric Motor Horsepower Rating:** 0.500 **Spindle Quantity:** Main Drive Type: Electric motor **Spindle Travel Distance:** 4.000 inches **Base Working Surface Length:** 10.000 inches **Base Working Surface Width:** 8.000 inches **Drilling Capability:** 1/2 in. Drilling capacity in cast iron **Column Type:** Round **Drill Chuck Size Accommodated:** 1/2 in. Key **Distance From Spindle Center To Column:** 7.500 inches

Base Working Surface Type: Tee slotted **Base Working Surface Shape:** Rectangular **Base Working Surface Mounting Location:** Base

NSN 3413-00-165-4136

Upright Drilling Machine - Page 2 of 3



Maximum Distance From Chuck/spindle Nose To Base Working Surface:
19.625 inches
Upper Working Surface Type:
Slotted
Upper Working Surface Shape:
Rectangular
Upper Working Surface Length:
12.000 inches
Upper Working Surface Width:
10.000 inches
Upper Working Surface Adjustment Feature:
Included
Upper Working Surface Vertical Adjustment:
Any acceptable
Swivel Adjustment In Deg:
Any acceptable
Tilt Adjustment Direction And Angle In Deg:
90.0 right err-100 err-100
Head Vertical Adjustment:
Any acceptable
Spindle Type:
Solid male tapered for drill chuck
Spindle Speed Quantity:
4
Spindle Speed Range In Rpm:
+475.0 to 1900.0
Upper Working Surface Mounting Location:
Column
Maximum Distance From Chuck/spindle Nose To Upper Working Surface:
14.250 inches
Voltage In Volts:
115.0 or 230.0
Phase:
Single
Frequency In Hertz:
60.0
Specification Or Standard:
1 type and a style and 1 size
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

NSN 3413-00-165-4136

Upright Drilling Machine - Page 3 of 3



Fiig:

T317-f