NSN 3413-00-165-4136

Upright Drilling Machine - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/3413-00-165-4136

Mounting Type:	
Bench	
Electric Motor Power Rating:	
0.500 horsepower	
Current Type:	
Ac	
Head Type:	
Sliding	
Fungus Resistant Treatment:	
Not included	
Radio Interference Shielding:	
Not provided	
Rotation Reversibility Feature:	
Not included	
Feed Type:	
Hand	
Electric Motor Horsepower Rating:	
0.500	
Spindle Quantity:	
1	
Main Drive Type:	
Electric motor	
Spindle Travel Distance:	
4.000 inches	
Base Working Surface Length:	
10.000 inches	
Base Working Surface Width:	
8.000 inches	
Drilling Capability:	
1/2 in. Drilling capacity in cast iron	
Column Type:	
Round	
Drill Chuck Size Accommodated:	
1/2 in. Key	
Distance From Spindle Center To Column:	
7.500 inches	
Base Working Surface Type:	
Tee slotted	
Base Working Surface Shape:	
Rectangular	
Base Working Surface Mounting Location:	
Base	

Upright Drilling Machine - Page 2 of 3



Maximum Distance From Chuck/spindle Nose To Base Working Surface:

19.625 inches

Upper Working Surface Type:

Slotted

Upper Working Surface Shape:

Rectangular

Upper Working Surface Length:

12.000 inches

Upper Working Surface Width:

10.000 inches

Upper Working Surface Adjustment Feature:

Included

Upper Working Surface Vertical Adjustment:

Any acceptable

Swivel Adjustment In Deg:

Any acceptable

Tilt Adjustment Direction And Angle In Deg:

90.0 right err-100 err-100

Head Vertical Adjustment:

Any acceptable

Spindle Type:

Solid male tapered for drill chuck

Spindle Speed Quantity:

4

Spindle Speed Range In Rpm:

+475.0 to 1900.0

Upper Working Surface Mounting Location:

Column

Maximum Distance From Chuck/spindle Nose To Upper Working Surface:

14.250 inches

Voltage In Volts:

115.0 or 230.0

Phase:

Single

Frequency In Hertz:

60.0

Specification Or Standard:

1 type and a style and 1 size

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 3413-00-165-4136

Upright Drilling Machine - Page 3 of 3

Fiig: T317-f

