NSN 3413-00-174-1542

Upright Drilling Machine - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3413-00-174-1542 **Mounting Type:** Bench **Electric Motor Power Rating:** 0.500 horsepower **Current Type:** Ac **Head Type:** Sliding **Fungus Resistant Treatment:** Not included **Radio Interference Shielding:** Not provided **Rotation Reversibility Feature:** Not included Feed Type: Hand **Electric Motor Horsepower Rating:** 0.500 **Spindle Quantity:** Main Drive Type: Electric motor **Spindle Socket Taper Size:** 2 morse **Spindle Travel Distance:** 7.750 inches **Base Working Surface Length:** 14.000 inches **Base Working Surface Width:** 14.000 inches **Drilling Capability:** 7/8 in mild steel **Column Type:** Box **Distance From Spindle Center To Column:** 8.000 inches **Base Working Surface Type:** Plain w/coolant trough **Base Working Surface Shape:**

Square **Base Working Surface Area:** Any acceptable

NSN 3413-00-174-1542Upright Drilling Machine - Page 2 of 2



Base Working Surface Mounting Location:
Base
Maximum Distance From Chuck/spindle Nose To Base Working Surface:
18.000 inches
Head Vertical Adjustment:
8.250 inches
Spindle Type:
Tapered socket
Spindle Speed Quantity:
5
Spindle Speed Range In Rpm:
+400.000 to 3000.000
Voltage In Volts:
220.0
Phase:
Three
Special Features:
440.0 volts
Frequency In Hertz:
60.000
Reference Number Differentiating Characteristics:
As differentiated by electric motor, spindle data, head and working surface
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T317-f